

CONNECTOR, FEMALE, 2X2-PIN, 24 V DC FOR ET200S,
INTERFACE MODULE, KP32F, PN/PN COUPLER, SPRING-
LOADED TERMINALS, INTERNALLY BRIDGED, COLOR-CODED
AMOUNT: SEE TECHNICAL DATA



Installation type/mounting	
Wall mounting/direct mounting possible	Yes; can be plugged into SIMATIC HMI device
Supply voltage	
Rated value (DC)	24 V; DC
Interfaces	
HMI-side interface	
• Number of pins HMI-side	2; Outgoing side jumpered internally, color-coded
Device-side interface	
• Number of pins device-side	4; Female, spring-loaded terminals 0.75 mm ²
Standards, approvals, certificates	
CE mark	Yes
Mechanics/material	
Design of housing	plastic
Dimensions	
Width	10 mm
Height	22 mm
Thickness	25 mm

Scope of supply	
Delivery quantity in pieces	10
Other	
Note:	for ET 200S, interface module, KP32F, PN-to-PN coupler
Usable in the following products	
• Product 1	6AV3688-3EH47-0AX0
• Product 2	6ES7158-3AD00-0XA0
• Product 3	6ES7158-3AD01-0XA0
last modified:	10/28/2016