

SIMATIC IFP1900 FLAT PANEL 19" DISPLAY (16:9),
MULTITOUCH, STANDARD VERSION MAX. 5M, 1366X768 PIXEL,
FOR 24V DC, DISPLAYPORT / DVI INTERFACE INCL. DVI/USB-
CABLE 1,8 M



Figure similar

General information	
Product type designation	IFP1900
Short designation	Flat Panel 19" multi-touch
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	18.5 in
Screen diagonal (cm)	47 cm
Display width	409.8 mm
Display height	230.4 mm
Viewing angle	170° x 160°
On Screen Display (OSD) configuration	No; Adjustable by means of software
Number of colors	16 777 216
Number of colors (bit levels)	24 bit
Resolution (pixels)	
• Resolution (WxH in pixel)	1366 x 768
• Horizontal image resolution	1 366 Pixel
• Vertical image resolution	768 Pixel

• Pixel size, horizontal	0.3 mm
• Pixel size, vertical	0.3 mm
General features	
• Detachable from computer unit	5 m
• Brightness/contrast	300 cd/m ² / 1000:1
• non-reflective and tempered mineral glass screen	Yes
• Luminance	300 cd/m ²
Backlighting	
• Type of backlighting	LED
• MTBF backlighting (up to 50%, at 25 °C)	50 000 h; At 25°C
• Backlight dimmable	Yes; 0-100 %
Control elements	
Keyboard fonts	
• Function keys	No
Touch operation	
• Monitor keyboard	Yes
Installation type/mounting	
Built-in unit	Yes; Portrait mode possible
• permissible angle to the vertical backward (console)	35°
• permissible angle to the vertical forward (ceiling mounting)	35°
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V; PELV
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Power loss	
Power loss AC	
• Typical	40 W
• Maximum	60 W
Power loss DC	
• Typical	40 W
• Maximum	65 W
Interfaces	
Video interfaces	
• DVI-D	Yes
• DisplayPort	Yes; DisplayPort V1.1
Touch interfaces	
• USB	Yes

Degree and class of protection	
IP65 at front	Yes
Enclosure Type 4 at the front	Yes
Enclosure Type 4x at the front	Yes
Enclosure Type 12 at the front	Yes
NEMA4 at the front	No
NEMA4X at the front	No
IP20 rear	Yes
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes; Corresponds to UL 508
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	
• Germanischer Lloyd (GL)	No
• American Bureau of Shipping (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (Class NK)	No
Use in hazardous areas	
• ATEX Zone 2	No; Available soon
• ATEX Zone 22	Yes; Available soon
• FM Class I Division 2	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	45 °C; Vertical installation (horizontal)
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	95 %; Non-condensing
Vibrations	
• Vibration load in operation	1 gn
• Vibration load during transport/storage	1 gn
Shock testing	
• Shock load during operation	15 gn
• Shock load during transport/storage	15 gn
Mechanics/material	
Type of housing (front)	Glass

Enclosure material (front)	
• Glass	Yes

Dimensions

Width of the housing front	483 mm
Height of housing front	337 mm
Mounting cutout, width	465 mm; Tolerance: +1 mm
Mounting cutout, height	319 mm; Tolerance: +1 mm
Overall depth	62.5 mm

Weights

Weight without packaging	5.5 kg
Weight incl. packaging	6.5 kg

last modified: 10/25/2016