

INPUT INTERFACE !!! PHASE-OUT PRODUCT !!! FOR FURTHER INFORMATION PLEASE CONTACT OUR SALES STAFF! TWO-TIER TERMINAL-TYPE COUPLING RELAY 1N0, GOLD-PLATED, AC/DC 24V SCREW TERMINAL WIDTH 6.2MM



Figure similar

General technical data:	
Type of voltage	AC/DC
Supply voltage frequency for auxiliary and control current circuit rated value	50 ... 60 Hz
Control supply voltage	
• at AC	
— at 50 Hz rated value	
— minimum	24 V
— maximum	24 V
— at 60 Hz rated value	
— minimum	24 V
— maximum	24 V
• at DC rated value	
— minimum	24 V
— maximum	24 V
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	1

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7004-2MB02>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7004-2MB02>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7004-2MB02&lang=en

last modified:

10/07/2016