

Product type designation

SIPLUS S7-1200 CM 1243-5
SIPLUS S7-1200 CM 1243-5; -25 ... +55 DEGREES C WITH
CONFORMAL COATING BASED ON 6GK7243-5DX30-0XE0 .
COMMUNICATION MODULE CM 1243-5, TO THE CONNECTION
OFF S7-1200 TO PROFIBUS AS A DP MASTER ASSEMBLY



Figure similar

Transmission rate	
Transfer rate	
• at the 1st interface / acc. to PROFIBUS	9.6 kbit/s ... 12 Mbit/s
Interfaces	
Number of interfaces / acc. to Industrial Ethernet	0
Number of electrical connections	
• at the 1st interface / acc. to PROFIBUS	1
• for power supply	1
Type of electrical connection	
• at the 1st interface / acc. to PROFIBUS	9-pin Sub-D socket (RS485)
• for power supply	3-pole terminal block
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage / external	24 V
Supply voltage / external / at DC / Rated value	24 V
Relative positive tolerance / at DC / at 24 V	20 %

Relative negative tolerance / at DC / at 24 V	20 %
Consumed current • from external supply voltage / at DC / at 24 V / typical	0.1 A
Power loss [W]	2.4 W

Permitted ambient conditions

Ambient temperature • during operation • for vertical installation / during operation • for horizontally arranged busbars / during operation • during storage • during transport	-25 ... +55 °C -25 ... +45 °C -25 ... +55 °C -40 ... +70 °C -40 ... +70 °C
Ambient condition / relating to ambient temperature - air pressure - installation altitude	-25 ... +55°C at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // -25 ... +45°C at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // -25 ... +35°C at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity / with condensation / maximum	100 %; r.F., incl. condensation/frost permitted (no commissioning in bedewed state)
Resistance to biologically active substances • conformity acc. to EN 60721-3-3	Yes; Compliance with EN 60721-3-3, Class 3B2 mold, fungus, and sponge spores (except fauna). The supplied plug covers must remain in place over the unused interfaces during operation!
Resistance to chemically active substances • conformity acc. to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3). The supplied plug covers must remain in place over the unused interfaces during operation!
Resistance to mechanically active substances • conformity acc. to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation!
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-1200 single width
Width	30 mm
Height	100 mm
Depth	75 mm
Net weight	0.134 kg
Mounting type • 35 mm DIN rail mounting • S7-300 rail mounting • wall mounting	Yes No Yes

Product properties, functions, components / general

Number of units • per CPU / maximum	1
---	---

Performance data / PROFIBUS DP

Service / as DP master	
• DPV1	Yes
Number of DP slaves / on DP master / usable	16
Amount of data	
• of the address area of the inputs / as DP master / total	512 byte
• of the address area of the outputs / as DP master / total	512 byte
• of the address area of the inputs / per DP slave	244 byte
• of the address area of the outputs / per DP slave	244 byte
• of the address area of the diagnostic data / per DP slave	240 byte
Service / as DP slave	
• DPV0	No
• DPV1	No

Performance data / S7 communication

Number of possible connections / for S7 communication	
• maximum	8
• with PG connections / maximum	1
• with PG/OP connections / maximum	3
• Note	max. 4 connections to other S7 stations

Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode	
• without DP / maximum	8
• with DP / maximum	8

Performance data / telecontrol

Protocol / is supported	
• TCP/IP	No
Configuration software	
• required	STEP 7 Basic/Professional V11 (TIA Portal) or higher

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter

- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

10/26/2016