

OUTPUT INTERFACE !!! PHASE-OUT PRODUCT !!! FOR FURTHER INFORMATION PLEASE CONTACT OUR SALES STAFF! TWO-TIER TERMINAL-TYPE OPTOCOUPPLERS 1N0, TRANSISTOR AC/DC 24-48V WITH MANUAL-0-AUTO SCREW TERMINAL WIDTH 12.5MM



Figure similar

General technical data:	
Type of voltage	DC
Control supply voltage	
• at DC rated value	
— minimum	
— maximum	24 V
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	1
Number of CO contacts for auxiliary contacts	0
Switching behavior	monostable
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Equipment marking acc. to DIN EN 61346-2	K
Mechanical data:	
Type of electrical connection	screw-type terminals
Type of electrical connection Plug-in socket	No
Design of the relay operating mechanism	poled

Design of the switching function positively driven	No
Product component Plug-in socket	No
Width	12.5 mm
Height	80 mm
Depth	86 mm

Ambient conditions:

Protection class IP	IP20
Ambient temperature during operation	-25 ... +60 °C

Certificates/ approvals:

General Product Approval		Declaration of Conformity	Test Certificates	other
 CCC	 UL	 EAC	 EG-Konf.	spezielle Prüfbescheinigungen sonstig

other

[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7004-3AC14>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7004-3AC14>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7004-3AC14&lang=en

last modified:

10/07/2016