



SIMATIC DP, ELECTRONIC MODULES FOR ET200PRO 4 DO DC 24V, 2.0A HIGH FEATURE, CHANNEL DIAGNOSTICS; SHORT CIRCUIT AND WIRE BREAK; INCLUSIVE BUS MODULE CONNECTING MODULE IO 6ES7194-4..00-0AA0 MUST BE ORDERED SEPERATELY

Supply voltage	
Load voltage 2L+	
• Rated value (DC)	24 V
• Short-circuit protection	Yes; per channel, electronic
• Reverse polarity protection	Yes; against destruction; load increasing
Input current	
from load voltage 2L+ (without load), max.	40 mA
from backplane bus 3.3 V DC, max.	30 mA
Power loss	
Power loss, typ.	2.5 W
Address area	
Address space per module	
• with packing	4 bit
• without packing	1 byte
Digital outputs	
Number of digital outputs	4
Short-circuit protection	Yes

• Response threshold, typ.	3 A
Limitation of inductive shutdown voltage to	2L+ (-47 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	10 W
Load resistance range	
• lower limit	12 Ω
• upper limit	4 k Ω
Output voltage	
• for signal "1", min.	2L+ (-0,8 V)
Output current	
• for signal "1" rated value	2 A
• for signal "0" residual current, max.	0.5 mA
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	1 Hz
Total current of the outputs (per group)	
all mounting positions	
— up to 55 °C, max.	4 A
Cable length	
• shielded, max.	30 m
• unshielded, max.	30 m
Interrupts/diagnostics/status information	
Diagnostic functions	Yes
Substitute values connectable	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnostic messages	
• Diagnostic information readable	Yes
• Wire-break	Yes
• Short-circuit	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital output (green)	Yes
• Channel fault indicator F (red)	Yes
Parameter	
Diagnostics wire break	channel by channel

Diagnostics short-circuit	channel by channel
Potential separation	
between backplane bus and all other circuit components	Yes
Potential separation digital outputs	
• between the channels	No
• between the channels and backplane bus	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Suitable for safety-oriented group deactivation	Yes
Highest safety class achievable in safety mode	
• Performance level according to ISO 13849-1	d
• SIL acc. to IEC 61508	2
Dimensions	
Width	45 mm
Height	130 mm
Depth	35 mm; without terminal module
Weights	
Weight, approx.	140 g
last modified:	10/28/2016