

SWITCH, D=70MM 100A 3NC



Figure similar

Model	
product brandname	SENTRON
Product designation	Off switches
Type of light source	Not applicable
Mounting type / for light source	Not applicable
Design of the switching function	Off switches
General technical data	
Number of poles	3
Short-circuit current rating	10 kA
Type of voltage	AC
Protection class	
Protection class IP	Other
Switching capacity	
Switching capacity current / rated value	0.3 kA
Dissipation	
Power loss [W]	

- for rated value of the current / at AC / in hot operating state / per pole
- maximum

5.5 W

16.5 W

Main circuit

Operating voltage / rated value

400 V

Operating current / rated value

100 A

Appearance

Color / of the lens

Not applicable

Product details

Product component / Signal lamp

No

Product function

Product function / positive opening (acc. to DIN VDE 0113)

No

Number

Number of NC contacts

0

Number of NO contacts

3

Number of CO contacts

0

Mechanical Design

Installation depth

70 mm

Number of width units

3

**General Product
Approval**

Test Certificates

other



[Typprüfbescheinigung/W
erkszeugnis](#)

[sonstig](#)

[Umweltbestätigung](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5TE8713>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5TE8713/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TE8713

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

