

Product type designation

CP 5623

COMMUNICATION PROCESSOR CP 5623 PCI EXPRESS X1 (3.3V) FOR CONNECTION TO PROFIBUS; INCL.DP-BASE SW,NCM PC: DP-RAM INTERF.F.DP-MASTER INCL. PG- AND FDL-PROTOCOL, SINGLE LICENSE F.1 INSTALLATION, R-SW, CLASS A;SW + ELECTR. MAN. ON CD 2-LANGUAGE (GER,ENG); SUPPORT FOR OPERATING SYSTEM SEE SIMATIC NET SW



Transmission rate

Transfer rate

- at the 1st interface / acc. to PROFIBUS 9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

- at the 1st interface / acc. to PROFIBUS 1

Type of electrical connection

- at the 1st interface / acc. to PROFIBUS 9-pin Sub-D socket (RS 485)

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage

- 1 / from backplane bus 3.3 V
- 2 / from backplane bus 12 V

Relative symmetrical tolerance / at DC

- at 3.3 V 9 %
- at 12 V 8 %

Consumed current

• 1 / from backplane bus / at DC / maximum	0.72 A
• 2 / from backplane bus / at DC / maximum	0.25 A
Power loss [W]	5.4 W

Permitted ambient conditions

Ambient temperature	
• during operation	5 ... 60 °C
• during storage	-20 ... +60 °C
• during transport	-20 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	85 %
Protection class IP	IP00

Design, dimensions and weight

Module format	PCI Express x1 (half length)
Width	21.6 mm
Height	126.3 mm
Depth	180.5 mm
Net weight	102 g
Number of plug-in cards of same design / plug-in / per PC station	4
Number of units / Note	FMS-5613 supports up to two CP 5603 / CP 5613 A2 / CP 5614 A2 / CP 5623 / CP 5624 processors

Performance data

Performance data / open communication

Software / for open communication / by means of SEND/RECEIVE / required	FDL driver included in scope of delivery of the CP
Number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	80

Performance data / PROFIBUS DP

Software / for DP master function / required	No
Service / as DP master	
• DPV0	Yes
• DPV1	Yes
• DPV2	Yes
Number of DP slaves / on DP master / usable	124
Amount of data	
• of the address area of the inputs / as DP master / total	30256 byte
• of the address area of the outputs / as DP master / total	30256 byte
• of the address area of the inputs / per DP slave	244 byte

• of the address area of the outputs / per DP slave	244 byte
• of the address area of the diagnostic data / per DP slave	244 byte
Software / for DP slave function / required	No
Service / as DP slave	
• DPV0	Yes
• DPV1	Yes
Amount of data	
• of the address area of the inputs / as DP slave / total	244 byte
• of the address area of the outputs / as DP slave / total	244 byte
Performance data / FMS functions	
Software / for FMS communication / required	Yes, FMS-5613
Number of possible connections / for FMS connection / maximum	40
Performance data / S7 communication	
Software / for S7 communication / required	Yes, HARDNET-PB S7 (S7-5613)
Number of possible connections / for S7/PG communication / maximum	50
Performance data / multi-protocol mode	
Number of active connections / with multi-protocol mode	50
Number of configurable connections / per PC station	207
Product functions / management, configuration	
Configuration software / required	Included in scope of supply
Product functions / Diagnosis	
Product function	
• Port diagnostics	Yes
Standards, specifications, approvals	
Standard	
• for EMC	2004/108/EC
• for safety / from CSA and UL	CAN/CSA C22.2 & UL 60950-1
• for emitted interference	EN 61000-6-3, EN 61000-6-4
• for interference immunity	EN 61000-6-1, EN 61000-6-2
Certificate of suitability	
• CE marking	Yes
• C-Tick	Yes
Further Information / Internet Links	
Internet-Link	

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<http://www.siemens.com/industrial-controls/mall>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

10/29/2016