

Data sheet

6GT2690-0AL00

Product type designation

Product description

Distance piece MDS D126 / MDS D426

Support for mounting transponders with 50 mm diameter and 25 mm distance to metal

MOBY D / RF300 ISO / RF200 SPACER FOR MDS D126 / D426 / 526; DIAMETER 60 MM; HEIGHT 30 MM; TEMPERATURE RANGE UP TO +85 °C PACKAGING UNIT = MINIMAL ORDER QUANTITY 50 PIECES



Suitability for use

Support is mounted with an M4 countersunk head screw, the transponder is snapped on

Mechanical data

Material

PA 6.6 GF

Color

black

Permitted ambient conditions

Ambient temperature

- during operation -25 ... +85 °C
- during storage -40 ... +100 °C
- during transport -40 ... +100 °C

Design, dimensions and weight

Height

30 mm

Diameter

59 mm

Further Information / Internet Links

Internet-Link

- to website: TIA Selection Tool
- to website: Selector SIMATIC NET
SELECTION TOOL
- to the website: IWLAN
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

last modified:

<http://www.siemens.com/tia-selection-tool>
<https://support.industry.siemens.com/WW/view/en/67384964>

<http://www.siemens.com/iwlan>
<http://www.siemens.com/ident/rfid>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

10/19/2016