

Product type designation

CP 443-5 Basic

COMMUNICATIONPROCESSOR CP 443-5 BASIC FOR
CONNECTION OF SIMATIC S7-400 TO PROFIBUS, FMS, S5
COMPATIBLE PG/OP AND S7 COMMUNICATION



Transmission rate

Transfer rate

- at the 1st interface / acc. to PROFIBUS 9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

0

Number of electrical connections

- at the 1st interface / acc. to PROFIBUS

1

Type of electrical connection

- at the 1st interface / acc. to PROFIBUS

9-pin Sub-D socket (RS485)

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Supply voltage

5 V

Relative symmetrical tolerance / at DC

- at 5 V

5 %

Consumed current

- from backplane bus / at DC / at 5 V / typical

1 A

• from external supply voltage / at DC / at 24 V / typical	1.2 A
Power loss [W]	5 W

Permitted ambient conditions

Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-400 single width
Width	25 mm
Height	290 mm
Depth	210 mm
Net weight	0.65 kg

Product properties, functions, components / general

Number of units	
• per CPU / maximum	14
• Note	depending on CPU type

Performance data / open communication

Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	32
Amount of data	
• as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum	240 byte

Performance data / FMS functions

Number of possible connections / for FMS connection / maximum	48
Amount of data / of the variables	
• for READ job / maximum	237 byte
• for WRITE job / maximum	233 byte
Number of variables	
• Configurable from server to FMS partner	512
• Loadable from server to FMS partner	2640

Performance data / S7 communication

Number of possible connections / for S7 communication	
---	--

- maximum

48

Performance data / multi-protocol mode

Number of possible connections / of which 2 reserved for PG/OP communication / with multi-protocol mode / maximum	59
Configuration software	
• required	STEP 7 V5.2 SP1 or higher and NCM S7 for PROFIBUS

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
----------------------	--

last modified:

10/21/2016