

Product type designation



SCALANCE W761-1 RJ45

IWLAN Access Point, SCALANCE W761-1 RJ45, 1 radio, 1 R-SMA antenna connector, IEEE 802.11a/b/g/h/n, 2,4/5GHz, brutto-data-rate 150 MBit/s, 1x RJ45 max. 100 MBit/s, DC 24 V, terminal block, IP20, 0... +55°C, WPA2/802.11i/e, Note national approvals! CERT ID: ELN-W1-RJ-E1, scope of supply: manuals on CD German/English, 1x terminal block; for use outside USA/Israel

Transmission rate

Transfer rate

- | | |
|---------------------------|--|
| • with WLAN / maximum | 150 Mbit/s |
| • for Industrial Ethernet | 10 Mbit/s, 100 Mbit/s, 10 Mbit/s, 100 Mbit/s |

Interfaces

Number of electrical connections

- | | |
|--|---|
| • for network components or terminal equipment | 1 |
| • for power supply | 1 |
| • for redundant voltage supply | 0 |

Type of electrical connection

- | | |
|--|-----------------------|
| • for network components or terminal equipment | RJ45 socket |
| • for power supply | 3-pole screw terminal |

design of the removable storage

- | | |
|------------|----|
| • C-PLUG | No |
| • KEY-PLUG | No |

Interfaces / wireless

Number of radio cards / permanently installed

1

Number of electrical connections / for external antenna(s)	1
Type of electrical connection / for external antenna(s)	R-SMA (socket)
Product feature / external antenna can be mounted directly on device	Yes

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage / 1 • from terminal block	19.2 V
Supply voltage / 2 • from terminal block	28.8 V
Consumed current • at DC / at 24 V / typical	0.15 A
Power loss [W] • at DC / at 24 V / typical	3.6 W

Permitted ambient conditions

Ambient temperature • during operation • during storage • during transport	0 ... 55 °C -40 ... +85 °C -40 ... +85 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Ambient condition / for operation	When used under hazardous conditions (Zone 2), the SCALANCE W761-1 RJ45 or W72x-1 RJ45 product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529.
Protection class IP	IP20

Design, dimensions and weight

Width	50 mm
Height	114 mm
Depth	74 mm
Width / of the enclosure / without antenna	50 mm
Height / of the enclosure / without antenna	114 mm
Depth / of the enclosure / without antenna	74 mm
Net weight	0.13 kg
Mounting type • S7-300 rail mounting • S7-1500 rail mounting • 35 mm DIN rail mounting • wall mounting	No No Yes No

Wireless frequencies

Operating frequency	
---------------------	--

- for WLAN in 2.4 GHz frequency band
- for WLAN in 5 GHz frequency band

2.41 ... 2.48 GHz

4.9 ... 5.8 GHz

Product properties, functions, components / general

Product function / Access Point Mode	Yes
Product function / Client Mode	Yes
Number of SSIDs	1
Product function	
• iPCF Access Point	No
• iPCF client	No
• iPCF-MC Access Point	No
• iPCF-MC client	No

Product functions / management, configuration

Number of manageable IP addresses / in client	4
Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• Configuration with STEP 7	Yes
• configuration with STEP 7 in the TIA Portal	Yes
• operation with IWLAN controller	No
• operation with Enterasys WLAN controller	No
• WDS	Yes
Protocol / is supported	
• Address Resolution Protocol (ARP)	Yes
• ICMP	Yes
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• DCP	Yes
• LLDP	Yes
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher-level designation/location designation	Yes

Product functions / Diagnosis

Product function	
• PROFINET IO diagnosis	No
• Link Check	No
• connection monitoring IP-Alive	No

• localization via Aeroscout	No
• SysLog	Yes
Protocol / is supported	
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes

Product functions / VLAN

Product function	
• function VLAN with IWLAN	Yes

Product functions / DHCP

Product function	
• DHCP client	Yes
• in Client Mode / DHCP server via LAN	Yes
• DHCP Option 82	Yes

Product functions / Redundancy

Protocol / is supported	
• STP/RSTP	Yes

Product functions / Security

Product function	
• ACL - MAC-based	Yes
• Management security, ACL-IP based	Yes
• IEEE 802.1x (radius)	Yes
• NAT/NAPT	No
• access protection according to IEEE802.11i	Yes
• WPA/WPA2	Yes
• TKIP/AES	Yes
Protocol / is supported	
• SSH	Yes
• RADIUS	Yes

Product functions / Time

Protocol / is supported	
• NTP	Yes
• SNTP	Yes
• SIMATIC Time	Yes

Standards, specifications, approvals

Standard	
• for FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4
• for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X

• for safety / from CSA and UL • for hazardous zone / from CSA and UL	UL 60950-1 CSA C22.2 No. 60950-1 ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, CL. 1, Div. 2, GP. A,B,C,D, T4 / CL. 1, Zone 2, GP IIC
Certificate of suitability	
• EC declaration of conformity • CE marking • C-Tick • CCC • E1 approval • Railway application in accordance with EN 50155 • NEMA TS2 • IEC 61375 • IEC 61850-3 • NEMA4X • Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af • Power-over-Ethernet according to IEEE802.3at for type 2	Yes Yes Yes No No No No No No No No No
Standard for wireless communication	
• IEEE 802.11a • IEEE 802.11b • IEEE 802.11e • IEEE 802.11g • IEEE 802.11h • IEEE 802.11i • IEEE 802.11n	Yes Yes Yes Yes Yes Yes Yes
Wireless approval	You will find the current list of countries at: www.siemens.de/funkzulassungen
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS) • Bureau Veritas (BV) • DNV GL • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS) • Royal Institution of Naval Architects (RINA)	No No No No No No No
Accessories	
accessories	24 V DC screw terminal included in scope of delivery
Further Information / Internet Links	
Internet-Link	

- to website: TIA Selection Tool
- to the website: IWLAN
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>

<http://www.siemens.com/iwlan>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

10/19/2016