

SWITCH DISCONNECTOR 3VT3 3-POLE; SWITCH
DISCONNECTOR IN= 630A RATED CURRENT WITHOUT
AUXILIARY RELEASE WITHOUT AUXILIARY/ALARM SWITCH



Model	
product brandname	SENTRON
Product designation	3VT1_5 molded case circuit breakers
Design of the operating mechanism	toggle handle
Type of the driving mechanism / motor drive	No
General technical data	
Number of poles	3
Size of the circuit-breaker	3VT3
Electrical endurance (switching cycles) / typical	5 000
Usage category	A
Performance class for circuit breaker	N
Mechanical service life (switching cycles) / typical	20 000
Operating frequency / maximum	120 1/h
Voltage	
Insulation voltage / rated value	690 V
Surge voltage resistance / rated value	8 kV
Protection class	
Protection class IP	IP40

Dissipation	
Power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	25 W
• maximum	75 W
Electricity	
Continuous current / rated value	630 A
Derating temperature / for the rated value of the continuous current	55 °C
Main circuit	
Operating frequency	
• 1 / rated value	50 Hz
• 2 / rated value	60 Hz
Operating voltage	
• rated value / maximum	690 V
• for main current circuit / at AC / at 50 Hz / maximum	690 V
• for main current circuit / at AC / at 60 Hz / maximum	690 V
• for main current circuit / at DC / maximum	250 V
Operating current	
• at 40 °C / rated value	630 A
• at 50 °C / rated value	630 A
• at 55 °C / rated value	600 A
• at 60 °C / rated value	600 A
• at 65 °C / rated value	540 A
• at 70 °C / rated value	540 A
Suitability	
Suitability for use	switch disconnecter
• Disconnecting means	Yes
Product details	
Product component	
• Trip indicator	No
• Auxiliary switch	No
• Voltage trigger	No
• undervoltage release	No
• undervoltage release with leading contact	No
Product extension / optional / motor drive	Yes
Product function	
Product function	

- Ground fault protection
- for neutral conductors / Short-circuit and overload proof
- Phase failure detection
- Overload protection

No
No
No
No

Short circuit

Operational short-circuit current breaking capacity (Ics)

- at 240 V / rated value
- at 415 V / rated value
- at 500 V / rated value
- at 690 V / rated value

40 kA
18 kA
10 kA
8 kA

Maximum short-circuit current breaking capacity (Icu)

- at 240 V / rated value
- at 415 V / rated value
- at 500 V / rated value
- at 690 V / rated value

60 kA
36 kA
20 kA
15 kA

Connections

- Arrangement of electrical connectors / for main current circuit
- Type of electrical connection / for main current circuit

front side
screw-type terminals

Mechanical Design

- Height
- Width
- Depth
- Mounting position
- Mounting type
- Net weight

275 mm
140 mm
117 mm
with vertical mounting surface +/-180° rotatable, with vertical mounting surface +/- 30° tiltable to the front and back
fixed mounting
6.2 kg

Environmental conditions

Ambient temperature

- during operation / minimum
- during operation / maximum
- during storage / minimum
- during storage / maximum

-40 °C
70 °C
-40 °C
70 °C

Certificates

Equipment marking

- acc. to DIN EN 61346-2
- acc. to DIN EN 81346-2

Q
Q

General Product Approval	Declaration of Conformity	Test Certificates	other
--------------------------	---------------------------	-------------------	-------



[Typprüfbescheinigung/Werkszeugnis](#)

[sonstig](#)

[Umweltbestätigung](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VT3763-2DE36-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VT3763-2DE36-0AA0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VT3763-2DE36-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



