

Product type designation

MDS D424 transponder

TRANSPONDER MDS D424 FOR RF200/ RF300 ISO/ MOBY D
 BUTTON ISO 15693 CHIP TYPE,FUJITSU MB89R118, 2000 BYTE
 FRAM USER MEMORY 27 X 4 MM (DXH); -25 UP TO +85 DGR C;
 MINIMAL ORDER QUANTITY 20 PCS



Wireless frequencies

Operating frequency / Rated value	13.56 MHz
-----------------------------------	-----------

Electrical data

Range / maximum	300 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
Protocol / with radio transmission	ISO 15693
Transfer rate / with radio transmission / maximum	26.5 kbit/s
Product feature / multitag-capable	Yes
Product component / Backup battery	No

Memory

Type of memory	FRAM
Storage capacity / of the user memory	2000 byte
Type of memory organization	UID (fixed code) 8 bytes, user memory 2000 bytes, configuration memory 40 bytes
Number of read cycles / at ambient temperature < 40 °C / maximum	1000000000000
Number of write cycles / at ambient temperature < 40 °C / maximum	1000000000000

Data retention time / at ambient temperature < 40 °C / not less than	10 y
Property of memory	Block-by-block write protection of the user memory
Type of transponder chip used	Fujitsu MB89R118

Mechanical data

Material	Epoxy resin
Color	black
Tightening torque / of the screw for securing the equipment / maximum	1 N·m
Mounting distance / relating to metal surfaces / recommended / minimum	15 mm

Permitted ambient conditions

Ambient temperature	
• during read/write access	-25 ... +85 °C
• outside the read/write area	-40 ... +100 °C
• during storage	-40 ... +100 °C
Protection class IP	IP67 / IPx9K
Shock resistance	According to DIN EN 60721-3-7 Class 7 M3
Shock acceleration	1000 m/s ²
Vibrational acceleration	200 m/s ²

Design, dimensions and weight

Height	4 mm
Diameter	27 mm
Net weight	5 g
Mounting type	M3 screw, gluing

Product properties, functions, components / general

Product feature	
• silicon-free	Yes
• printable	No

Standards, specifications, approvals

MTBF	171 y
------	-------

Accessories

accessories	Mounting support and spacer
-------------	-----------------------------

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	https://support.industry.siemens.com/cs/ww/en/view/67384964
• to website: Industrial communication	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter

- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

last modified:

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

10/15/2016