

SIMATIC DP, ELECT. SUBMODULE FOR ET 200ISP, 4 DO, DC
17,4V/27MA, "H"-SHUT DOWN



Input current	
from load voltage L+ (without load), max.	300 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	2.1 W
Address area	
Address space per module	
• without packing	2 byte
Digital outputs	
Number of digital outputs	4; additionally 1 intrinsically-safe input for H shutdown
Short-circuit protection	Yes
No-load voltage U _{ao} (DC)	17.4 V
Internal resistor R _i	150 Ω
Trend key points E	
• Voltage U _e (DC)	13.3 V
• Current I _e	27 mA
Output current	
• for signal "1" rated value	0.027 A

Output delay with resistive load	
• "0" to "1", max.	2 ms
• "1" to "0", max.	1.5 ms
Parallel switching of two outputs	
• for uprating	Yes
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	2 Hz
Cable length	
• shielded, max.	500 m
• unshielded, max.	500 m
Interrupts/diagnostics/status information	
Status indicator	Yes
Alarms	No
Diagnostic functions	Yes
Alarms	
• Diagnostic alarm	Yes; Parameterizable
Diagnostic messages	
• Diagnostic information readable	Yes
• Wire-break	Yes
• Short-circuit	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital output (green)	Yes
Parameter	
Remark	14 byte
Diagnostics wire break	Yes
Diagnostics short-circuit	Yes
Response to CPU/master STOP	Substitute a value/keep last value
Ex(i) characteristics	
Maximum values of output circuits (per channel)	
• Ta (permissible ambient temperature), max.	70 °C
Potential separation	
Potential separation digital outputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
Standards, approvals, certificates	
Use in hazardous areas	

- Type of protection acc. to EN 50020 (CENELEC)
- Type of protection acc. to KEMA

II2 G (1) GD Ex ib[ia] IIC T4 and I M2 Ex ib[ia] I

04 ATEX 1249

Dimensions

Width	30 mm
Height	129 mm
Depth	136.5 mm

Weights

Weight, approx.	255 g
-----------------	-------

last modified: 10/28/2016