

SINAMICS LINE REACTOR FOR 10 KW SMART LINE MODULE
INPUT: 3-PH 380-480 V, 50/60 HZ



Figure similar

Order number	
Phase number / of the input voltage	3
Type of voltage / of the input voltage	AC
Input voltage	380 ... 480
Output current / rated value	28 A
Power loss [W]	
• at 50 Hz	Wert fehlt!
• at 60 Hz	Wert fehlt!
Type of electrical connection	
• for mains supply line	screw-type terminal
• for load-side outgoing feeder	screw terminals
Type of connectable conductor cross-section / for load-side outgoing feeder	Wert fehlt!
Connectable conductor cross-section	
• for mains supply line	Wert fehlt!
• for load-side outgoing feeder	10 mm²
Type of electrical connection / for PE conductor	Screw-type terminals
Protection class IP	IP20

Width	177 mm
Height	196 mm
Depth	110 mm
Net weight	7.5 kg
Certificate of suitability	cURus

Further information

Information und Download Center

https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx

Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/6SL3000-0CE21-0AA0/all>

Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SL3000-0CE21-0AA0/all>