

Product type designation

RF340T transponder

SIMATIC RF300 TRANSPONDER RF340T 8 KBYTE FRAM, IP 67/X9K, -25 UP TO +85 DEGR/C 48 MM X 25 MM X 15 MM, MIN.
ORDER QUANTITY 5 PCS



Wireless frequencies

Operating frequency / Rated value	13.56 MHz
-----------------------------------	-----------

Electrical data

Range / maximum	105 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
Protocol / with radio transmission	RF300-specific
Transfer rate / with radio transmission / maximum	106 kbit/s
Product feature / multitag-capable	Yes
Product component / Backup battery	No

Memory

Type of memory	FRAM/EEPROM
Storage capacity / of the user memory	8189 byte
Type of memory organization	UID (fixed code) 4 bytes, user memory 8189 bytes, OTP memory 20 bytes
Number of read cycles / at ambient temperature < 40 °C / maximum	10000000000
Number of write cycles / at ambient temperature < 40 °C / maximum	10000000000

Data retention time / at ambient temperature < 40 °C / not less than	10 y
Property of memory	Block-by-block write protection of the OTP memory

Mechanical data

Material	PA12
Color	anthracite
Mounting distance / relating to metal surfaces / recommended / minimum	0 mm

Permitted ambient conditions

Ambient temperature	
• during read/write access	-25 ... +85 °C
• outside the read/write area	-40 ... +85 °C
• during storage	-40 ... +85 °C
Protection class IP	IP67 / IPx9K
Shock resistance	According to DIN EN 60721-3-7 Class 7 M3
Shock acceleration	500 m/s ²
Vibrational acceleration	200 m/s ²

Design, dimensions and weight

Width	25 mm
Height	15 mm
Depth	48 mm
Net weight	25 g
Mounting type	2 x M3 screws

Product properties, functions, components / general

Product feature	
• silicon-free	Yes
• printable	No

Standards, specifications, approvals

MTBF	1200 y
------	--------

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	https://support.industry.siemens.com/cs/ww/en/view/67384964
• to website: Industrial communication	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
last modified:	10/12/2016