



INTERFACE WITH LED FOR SWITCH POSITION
WITH SURGE SUPPRESSION FOR MOUNTING
ONTO CONTACTORS: 2TF30 TO 3TF35, 3TF40 TO
3TF45

Figure similar

General technical data:		
Product component protective wiring		No
Control circuit/ Control:		
Type of voltage of the control supply voltage		DC
Control supply voltage 1		
• at DC		
— rated value	V	24
Installation/ mounting/ dimensions:		
Mounting type		screw and snap-on mounting
Certificates/ approvals:		

General Product Approval			Declaration of Conformity	Test Certificates	
				Typprüfbescheinigung/Werkszeugnis	sonstig
CSA	UL		EG-Konf.		

Shipping Approval	other	
		Bestätigungen
PRS	RINA	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX4090-0D>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX4090-0D>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX4090-0D&lang=en

last modified:

10/07/2016