

MICROMASTER 4 COMMUTATING CHOKE 200-480 V 3AC 53,6A
FOOTPRINT FSD - 0.29 MH



Figure similar

Order number	
Phase number / of the input voltage	3
Type of voltage / of the input voltage	AC
Input voltage	200 ... 480
Output current / rated value	53.6 A
Power loss [W]	
• at 50 Hz	Wert fehlt!
• at 60 Hz	Wert fehlt!
Type of electrical connection	
• for mains supply line	screw-type terminal
• for load-side outgoing feeder	Pigtail
Type of connectable conductor cross-section / for load-side outgoing feeder	Wert fehlt!
Connectable conductor cross-section	
• for mains supply line	Wert fehlt!
• for load-side outgoing feeder	16 mm²
Wire length / of connecting cable / for load-side outgoing feeder	0.79 m

Type of electrical connection / for PE conductor	M8 stud
Protection class IP	IP20
Width	275 mm
Height	520 mm
Depth	83.5 mm
Net weight	13 kg
Certificate of suitability	cURus

Further information

Information und Download Center

https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx

Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/6SE6400-3CC05-2DD0/all>

Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SE6400-3CC05-2DD0/all>