



SITOP REDUNDANCY MODULE
SITOP PSE202U REDUNDANCY MODULE INPUT/OUTPUT: 24
V/40 A DC CAN BE USED FOR DECOUPLING OF 2 SITOP
POWER SUPPLIES WITH 20 A MAX. OUTPUT CURRENT EACH

Input	
Input	DC voltage
Supply voltage	
• at DC	24 ... 24 V
Input voltage	
• at DC	24 ... 28.8 V
Output	
Output	Controlled, isolated DC voltage
Rated voltage Vout DC	24 V
Output voltage	Vin - approx. 0.5 V
Product function Output voltage adjustable	No
Status display	Green LED for "both Input voltages > switching threshold"; red LED: for "at least one input voltage < switching threshold"
Signaling	Isolated relay contact (changeover contacts, rating 8 A/240 V AC, 24 V DC): Signals OK if both input voltages > switching threshold, setting range of threshold 20 ... 25 V
Rated current value Iout rated	40 A
Current range	40 A
• Note	max. aggregate current 40 A

Safety	
Galvanic isolation	yes, SELV acc. to EN 60950-1 (relay contact)
Protection class	Class I
CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
Explosion protection	IECEx Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nAC IIC T4; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T4
FM approval	-
CB approval	No
Marine approval	GL, ABS
Degree of protection (EN 60529)	IP20

EMC	
Emitted interference	EN 55022 Class B
Noise immunity	EN 61000-6-2

Operating data	
Ambient temperature	
during operation	-25 ... +60 °C
— Note	with natural convection
during transport	-40 ... +85 °C
during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation

Mechanics	
Connection technology	screw-type terminals
Connections	
Supply input	Input, output and ground: 1 screw terminal each for 0.33 ... 10 mm ² single-core/finely stranded
Auxiliary	Relay contact: 3 screw terminals for 0.5 ... 2.5 mm ² single-core/finely stranded
Width of the enclosure	70 mm
Height of the enclosure	125 mm
Depth of the enclosure	125 mm
Required spacing	
top	50 mm
bottom	50 mm
left	0 mm
right	0 mm
Weight, approx.	0.5 kg
Product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
MTBF at 40 °C	6 471 654 h

