

SIMATIC S7-400, SM 422 DIGITAL OUTPUT MODULE, OPTIC.
ISOLATED, 32 DO, 24V DC, 0.5A



Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
Input current	
from load voltage L+ (without load), max.	30 mA
from backplane bus 5 V DC, max.	200 mA
Power loss	
Power loss, typ.	4 W
Digital outputs	
Number of digital outputs	32
Limitation of inductive shutdown voltage to	-27 V
Switching capacity of the outputs	
• on lamp load, max.	5 W
Output voltage	

• for signal "1", min.	L+ (-0.3 V)
Output current	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, min.	5 mA
• for signal "1" permissible range, max.	0.6 A
• for signal "0" residual current, max.	0.3 mA
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
Total current of the outputs (per group)	
all mounting positions	
— up to 60 °C, max.	2 A; 8 adjacent outputs each
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Potential separation	
Potential separation digital outputs	
• between the channels, in groups of	32
• between the channels and backplane bus	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	25 mm
Height	290 mm
Depth	210 mm
Weights	
Weight, approx.	600 g
last modified:	10/28/2016