

SIPLUS ET200S EM 1SI RS232/422 -25 ... +70 DEGREES C WITH CONFORMAL COATING BASED ON 6ES7138-4DF11-0AB0 .
SERIAL INTERFACE ONE CHANNEL, 15MM WIDE RS232/422, 485 MODBUS/USS



Figure similar

Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes
Input current	
from supply voltage L+, max.	80 mA; Typ. 20 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	1.2 W
Memory	
Standard blocks	11 100 byte; Modbus: S_SEND 2700, S_RCV 2400, S_MODB 6000; USI: S_SEND 2700, S_RCV 2400, S_USST 1900, S_USSR 2600, S_USSI 1500
Interfaces	
Number of interfaces	1
Interface physics, RS 232C (V.24)	Yes; RS 232C signals: 8 (TxD, RxD, RTS, CTS, DTR, DSR, DCD, PE)

Interface (physical) RS 422/485 (X.27)	Yes; RS-422 signals: 5 (TxD(A), RxD(A), TxD(B), RxD(B), PE); RS-485 signals: 3 (R/T(A), R/T(B), PE)
RS 232, cable length shielded, max.	15 m
RS 422/RS 485, cable length shielded, max.	1 200 m
Point-to-point	
Integrated protocol driver	
— Modbus	Yes
— Transmission rate, Modbus protocol, max.	115.2 kbit/s; half duplex: 110, 300, 600, 1 200, 2 400, 4 800, 9 600, 19 200, 38 400, 57 600, 76 800, 115 200 bps
— USS	Yes
— Transmission rate, USS protocol, max.	115.2 kbit/s; half duplex: 110, 300, 600, 1 200, 2 400, 4 800, 9 600, 19 200, 38 400, 57 600, 76 800, 115 200 bps
Character frame (adjustable)	
— Bits per character	8
— Number of start/stop bits	1 or 2 (USS only 1)
— Bits per character frame	10 or 11 (USS only 11 bits)
— Parity	none, odd, even (USI even only)
Data quantity per PLC sampling cycle	
— Send	32 byte; with IM151-1 Standard as of 6ES7 151-1AA04-0AB0; with IM151-1 High Feature as of 6ES7 151-1BA01-0AB0; otherwise 8 bytes
— Receive	32 byte; with IM151-1 Standard as of 6ES7 151-1AA04-0AB0; with IM151-1 High Feature as of 6ES7 151-1BA01-0AB0; otherwise 8 bytes
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• Receive RxD (green)	Yes
• Transmit TxD (green)	Yes
• Group error SF (red)	Yes
Potential separation	
Potential separation interface	
• Between RS 422/485 and internal power supply	Yes
• between RS 232 and internal power supply	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C; = Tmin
• max.	70 °C; = Tmax
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Extended ambient conditions	

- relative to ambient temperature-atmospheric pressure-installation altitude

Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)

Relative humidity

- With condensation, tested in accordance with IEC 60068-2-38, max.

100 %; Relative humidity, incl. condensation / frost permitted (no commissioning under condensation conditions)

Resistance

- against biologically active substances / conformity with EN 60721-3-3
- against chemically active substances / conformity with EN 60721-3-3
- against mechanically active substances / conformity with EN 60721-3-3

Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!

Yes; Class 3C4 incl. salt spray according to EN 60068-2-52 (degree of severity 3). The supplied connector covers must remain on the unused interfaces during operation!

Yes; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!

Dimensions

Width	15 mm
Height	81 mm
Depth	52 mm

Weights

Weight, approx.	50 g
-----------------	------

last modified: 10/28/2016