

AS-INTERFACE DISTRIB. COMPACT FOR CREATING
NETWORK STRUCTURES BRANCHES,
DISCONNECTION, IP 67/68/69K, MAX. 8A



Figure similar

General technical data:		
Type of device		AS-Interface accessories
Design of the product		AS-i compact distribution boards
Function		distribution function for AS-i flat cables
operating voltage according to AS-Interface specification	V	26.5 ... 31.6
Note		cable must not end in the distribution board
Note 1		cable must not end in the distribution board
Connections/ Terminals:		
connection		insulation piercing method for AS-Interface flat cable
Connection system		insulation piercing method for AS-Interface flat cable
Mechanical data:		
Type of mounting		screw fixing
Contacts Load rating max	A	8
Ambient conditions:		
ambient temperature	°C	-25 ... +75

ambient temperature when stored	°C	-25 ... +85
degree of protection		IP67/68/69K

Certificates/ approvals:

General Product Approval	Functional Safety/Safety of Machinery	Declaration of Conformity	Shipping Approval
--------------------------	---------------------------------------	---------------------------	-------------------



[sonstig](#)



Shipping Approval	other
-------------------	-------



[Bestätigungen](#)

[Umweltbestätigung](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1901-1NN10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1901-1NN10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1901-1NN10&lang=en



last modified:

09/15/2016

