



piconet® extension module for IP-Link
2-channel pulse width modulation (PWM)
SNNE-0002D-0002




- Pulse width modulation
- 2-channel
- 2.5 A per channel
- Direct connection to the IP link
- Fibre-glass reinforced housing
- Encapsulated module electronics
- Metal connector
- Degree of protection IP67

Wyjście M12 × 1



Zasilanie M8 × 1



Typ	SNNE-0002D-0002
Nr kat.	6824177
Liczba kanałów	2
Napięcie pracy / obciążenia	20...29 VDC
Prąd pracy	≤ 25 mA
Fibre-optic length	≤ 15 m
V/R output	0.5 A short-circuit proof
Prąd wyjściowy na kanał	2.5
Typ obciążenia	resistive, inductive
Base frequency	1 Hz...10 kHz (default 250 Hz)
Duty factor	0...100 % (t ON > 750 ns, t OFF > 500 ns)
Rozdzielczość	10 Bit
Freewheeling diode	on the outputs
Dimensions (W x L x H)	30 x 126 x 26.5mm
Temperatura pracy	0...+55 °C
Temperatura składowania	-25 to 85 °C
Test wibracyjny	as per EN 60068-2-6
Test przeciążeniowy/wstrząsowy	acc. to DIN EN 60068-2-27
Kompatybilność elektromagnetyczna	according to EN 61000-6-2/EN 61000-6-4
Klasa ochrony	IP67
Certyfikaty	CE, cULus

piconet® extension module for IP-Link
2-channel pulse width modulation (PWM)
SNNE-0002D-0002

TURCK

Industrial
Automation

Dane z odwzorowania procesu

	Address	Input data		Output data	
Pre-conditions	Word	High-Byte	Low-Byte	High-Byte	Low-Byte
Complex mapping: Data are mapped with control and status byte	0	Ch0 Reg1	SB0	Ch0 D1	CB0
	1	SB1	Ch0 Reg0	CB1	Ch0 D0
	2	Ch1 Reg0	Ch1 Reg1	Ch1 D0	Ch1 D1