

0034 190	DATA SHEET	
valid from: 01.01.2019	JE-Y(ST)Y...BD	

Application

JE-Y(ST)Y...BD is a connecting cable for industrial electronics. It can be used in measurement and control engineering and also as pulse and data transmission cable.

The cable is intended for use in dry and damp interiors and for fixed installation.

Design

Design	Design in accordance with DIN VDE 0815, Table 4, Type JE-Y(ST)Y...BD Electrical properties in accordance with DIN VDE 0815, Table 10, Type JE-Y(ST)Y...BD Tests at the cable in accordance with DIN VDE 0815, Tabelle 21
Certification	Classification of fire behaviour according to EN 13501-6 and EN 50575 (article/dimension range see www.lappkabel.com/cpr)
Outer sheath	Colour of the sheath: pebble grey (similar RAL 7032)

Diameter of the outer sheath

Article number	Dimension	Outer sheath $\varnothing$
0034190	2 x 2 x 0.8 mm	ca. 6.0 mm
0034191	4 x 2 x 0.8 mm	ca. 8.5 mm
0034192	8 x 2 x 0.8 mm	ca. 11.0 mm
0034193	12 x 2 x 0.8 mm	ca. 13.0 mm
0034194	16 x 2 x 0.8 mm	ca. 14.5 mm
0034195	20 x 2 x 0.8 mm	ca. 16.0 mm
0034197	40 x 2 x 0.8 mm	ca. 22.0 mm

Electrical properties at 20°C

Loop resistance	max. 73.2 Ω /km
Insulation resistance	min. 100 M Ω /km
Mutual capacitance	max. 100 nF/km (at 800 Hz)
Inductance	ca. 0.65 mH/km
Capacitive coupling	max. 200 pF/100 m (at 800 Hz)
Peak operating voltage	225 V (not for power applications)
Test voltage	C/C: 500 V C/S: 2000 V

Mechanical and thermal properties

Minimum bending radius	Fixed installation: 6 x cable $\varnothing$
Temperature range	Occasional flexing: - 5 °C up to +50 °C Fixed installation: - 30 °C up to +70 °C
Flammability	flame retardant acc. to IEC 60332-1-2
General requirements	These cable are conform to the EU-Directive 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances). These cables (see www.lappkabel.com/cpr) are classified in accordance with the EU-Regulation no. 305/2011 (CPR).

Creator: PESA / PDC	Document: DB0034190EN	Page 1 of 1
Released: ALTE / PDC	Version: 05	