

|                           |                               |                                                                                     |
|---------------------------|-------------------------------|-------------------------------------------------------------------------------------|
| 1313852                   | <b>DATA SHEET</b>             |  |
| valid from:<br>01.01.2019 | <b>ÖLFLEX® CLASSIC 400 CP</b> |                                                                                     |

## Application

ÖLFLEX® CLASSIC 400 CP cables are oil resistant connection and control cables with a Polyurethan outer sheath, for flexible use and fixed installation for medium mechanical abuse. They are also suitable for use in dry, damp or wet areas. They are suitable for outdoor use if the indicated temperature range is observed.

ÖLFLEX® CLASSIC 400 CP cables are increased resistant to oils and at room temperature largely resistant to acids and alkalis. The outer sheath withstands high mechanical stresses, in particular abrasion and dragging. It is also cut proof and resists microbes and hydrolysis. They are suitable for occasional, non-automated movements. The maximum tensile load is 15 N/mm<sup>2</sup> of conductor cross-section during installation and operation. Compulsory guidance is not permitted. The screening braid protects against interference from electrical fields.

Application range:

Industrial machinery, machine tools, measurement-, control-, electrical applications, food production and packaging machinery.

## Design

|                          |                                                                                                                                     |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Design                   | based on<br>EN 50525-2-51 resp. VDE 0285-525-2-51<br>EN 50525-2-21 resp. VDE 0285-525-2-21                                          |
| Conductor                | fine wire strands of bare copper, acc. to IEC 60228 resp. VDE 0295, Class 5                                                         |
| Insulation               | LAPP special PVC compound P8/1, better than the PVC compound TI2, acc. to EN 50363-3 resp. VDE 0207-363-3                           |
| Core identification code | acc. to VDE 0293-1, with or without GN/YE ground conductor<br>black cores with whit numbers acc. to DIN EN 50334 resp. VDE 0293-334 |
| Inner sheath             | PVC compound TM2 acc. to EN 50363-4-1 resp. VDE 0207-363-4-1                                                                        |
| Screen                   | braid of tinned copper, coverage = 85 % (nominal value)                                                                             |
| Outer sheath             | Polyurethane compound TMPU acc. to EN 50363-10-2 resp. VDE 0207-363-10-2<br>colour: silver grey, similar RAL 7001                   |

## Electrical properties at 20°C

|                             |                                                |
|-----------------------------|------------------------------------------------|
| Specific volume resistivity | > 20 GΩ x cm                                   |
| Transfer impedance          | max. 250 mΩ/m (at 30 MHz)                      |
| Rated voltage               | U <sub>o</sub> / U: 300 / 500 V                |
| Test voltage                | Core/Core: 4000 V AC<br>Core/Screen: 4000 V AC |

## Mechanical and thermal properties

|                        |                                                                                                                                               |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Minimum bending radius | occasional flexing: 12,5 x cable diameter<br>fixed installation: 4 x cable diameter                                                           |
| Temperature range      | occasional flexing: - 5 °C up to +70 °C max. conductor temp.<br>fixed installation: - 40 °C up to +80 °C max. conductor temp.                 |
| UV resistance          | acc. to EN 50618 resp. VDE 0283-618<br>acc. to EN 50620 resp. VDE 0285-620<br>acc. to EN ISO 4892-2-2013, method A (change of colour allowed) |
| Ozone resistance       | acc. to EN 50396 resp. VDE 0473-396, method B                                                                                                 |
| Oil resistance         | acc. to EN 50363-10-2 resp. VDE 0207-363-10-2                                                                                                 |
| Tests                  | acc. to IEC 60811, EN 50395, EN 50396                                                                                                         |
| General requirements   | These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive)                                                               |

|                      |                       |             |
|----------------------|-----------------------|-------------|
| Creator: LABU / PDC  | Document: DB1313852EN | Page 1 of 1 |
| Released: ALTE / PDC | Version: 06           |             |