

2170002	DATA SHEET	
valid from: 01.01.2019	RG-178 B/U	

Application

RG-178 B/U are coaxial cables for radio and computer systems, as well as applications related to commercial radio-frequency (high frequency) technology and electronics.

They allow distortion-free and low-attenuation transmission of signals with a high bandwidth over shorter distances.

The cable is intended for limited movements and for fixed installation in dry and damp interiors and outdoors. It meets the requirements concerning high ambient temperatures and chemical stress.

Design

Design	Cable design and electrical properties of M17/93-RG178 to MIL-C-17. Designation in accordance with MIL-DTL-17 H: M17/140-00001
Conductor	Inner conductor: steel wire, copper plated silver 7x0.102 mm (30AWG/0.057 mm ²) Ø: 0.30 ± 0.025
Insulation	PTFE, 0.86 mm Ø
Screen	Outer conductor: braid silvered copper wires coverage 96 % (nominal value)
Outer sheath	FEP, transparent brown Outer diameter: 1.81 ± 0.13 mm

Electrical properties at 20°C

Conductor resistance	Inner conductor: max. 802 Ω/km
Insulation resistance	min. 10 GΩ x km
Mutual capacitance	max. 95 pF/m (1 kHz)
Characteristic impedance	50 ± 2 Ω
Attenuation	max. 63 dB/100 m (200 MHz) max. 93 dB/100 m (400 MHz)
Velocity of propagation	70 %
Rated voltage	0.7 kV (50 Hz)
Test voltage	2 kV

Mechanical and thermal properties

Minimum bending radius	occasional flexing: 10 x cable Ø fixed installation: 6 x cable Ø
Temperature range	fixed installation: -55 °C up to 250 °C
General requirements	This cable is conform to the EU-Directive 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances).

Creator: PESA / PDC	Document: DB2170002EN	Page 1 of 1
Released: ALTE / PDC	Version: 05	