

44423026	DATA SHEET	
Valid from: 17.09.2018	EPIC® H-B 10 AGS-LB	

Description

- Small angle housing for drives and control cabinets with single lever.



General Characteristics

Series	H-B 10
Version	Panel mount base, angled
Locking	Single lever
Protection (DIN EN 60529)	IP 65 (latched)
Protection (NEMA 250, UL50E)	12 (latched)
Temperature Range	-40°C to +100°C, short term up to +125°C

Materials and Surfaces

Housing	Aluminium alloy, powder-coated, grey
Bolt	Heat-treatable steel, zinc-plated
Lever	Steel, zinc-plated
Profile Seal	NBR

Approvals

VDE-Approval, VDE-REG.-Nr.	B437
----------------------------	------


Standard

Safety Standard	IEC 61984
-----------------	-----------


Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB44423026EN Version: 01	Page 1 of 3
---	---------------------------------------	-------------

44423026	DATA SHEET	
Valid from: 17.09.2018	EPIC® H-B 10 AGS-LB	

Technical Drawings



Montageausschnitt
Panel cut-out



Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB44423026EN Version: 01	Page 2 of 3
---	---------------------------------------	-------------

44423026	DATA SHEET	
Valid from: 17.09.2018	EPIC® H-B 10 AGS-LB	



Automation



Industrial machinery and plant engineering



Mechanical resistance



Robust



Waterproof

Info

Universal, robust metal housings size H-B 10
Housing for motor termination

Application range

Plant engineering
Drive systems
Light & sound technology
Plastics industry

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB44423026EN Version: 01	Page 3 of 3
---	---------------------------------------	-------------