

44423100	DATA SHEET	
Valid from: 28.03.2019	EPIC® M17 SIGNAL D6	

Description:

Cable connector straight
 SPEEDCON-Lock, M17
 Number of pins: 8 or 17
 Contact type: male/female, Crimp connection
 Sealing: O-Ring axial
 Shielded: yes
 Cable diameter: 3, 5 mm – 11 mm



Product variations:

Article number	Typ	Pin-arrangement	PU
44423100	female	8 Pin	5
44422102	male	8 Pin	5
44423101	female	17 Pin	5
44423103	male	17 Pin	5

General characteristics:

Connector type	Cable connector
Number of pins	8 / 17
Connector lock	Speedcon
Cable diameter	3,5 mm – 11 mm
Termination method	Crimp termination
Upper temperature limit	+ 125 °C
Lower temperature limit	- 40 °C
Contacts, base material	CuZn (brass)
Contacts, surface	Au (gold)
Insert material	PA
Housing material	Zinc die-casting, nickel plated
Sealing material	FPM
Protection class	IP 67
Pollution degree	3
Overvoltage category	III
Cycles of mechanical operation	>100

44423100	DATA SHEET	
Valid from: 28.03.2019	EPIC® M17 SIGNAL D6	


Version 8 Pin

Electrical characteristics:


Rated voltage	60 V
Rated impulse voltage	1500 V
Rated current (25°C)	3,6 A
Contact diameter	1 mm
Termination cross-section	0, 06 mm² – 1, 0 mm²

Pin-arrangement:

Female



Male



Fitting female contacts (contacts must be ordered separately)



Lapp Art. No.	Description
44423122:	Crimp contact, drilled, contact diameter: 1 mm, termination cross-section: 0, 06 mm²...0, 25 mm²
44423123:	Crimp contact, drilled, contact diameter: 1 mm, termination cross-section: 0, 34 mm²...0, 5 mm²
44423124:	Crimp contact, drilled, contact diameter: 1 mm, termination cross-section: 0, 5 mm²...1 mm²

Fitting male contacts (contacts must be ordered separately)



Lapp Art. No.	Description
44423130:	Crimp contact, drilled, contact diameter: 1 mm, termination cross-section: 0, 06 mm²...0, 25 mm²
44423131:	Crimp contact, drilled, contact diameter: 1 mm, termination cross-section: 0, 34 mm²...0, 5 mm²
44423132:	Crimp contact, drilled, contact diameter: 1 mm, termination cross-section: 0, 5 mm²...1 mm²

Creator: STKU3/PDP Released: IVSE1/PDP	Document: DB44423100EN Version: 02	Page 2 of 4
---	---------------------------------------	-------------

44423100	DATA SHEET	
Valid from: 28.03.2019	EPIC® M17 SIGNAL D6	


Version 17 Pin

Electrical characteristics:


Rated voltage	60 V
Rated impulse voltage	1500 V
Rated current (25°C)	3,6 A
Contact diameter	0,6 mm
Termination cross-section	0,06 mm² – 0,5 mm²

Pin-arrangement:

Female



Male



Fitting female contacts (contacts must be ordered separately)



Lapp Art. No.	Description
44423125:	Crimp contact, drilled, contact diameter: 0, 6 mm, termination cross-section: 0,06 mm²...0,25 mm²
44423126:	Crimp contact, drilled, contact diameter: 0, 6 mm, termination cross-section: 0,06 mm²...0,34 mm²
44423127:	Crimp contact, drilled, contact diameter: 0, 6 mm, termination cross-section: 0,34 mm²...0,5 mm²


Fitting male contacts (contacts must be ordered separately)



Lapp Art. No.	Description
44423133:	Crimp contact, drilled, contact diameter: 0,6 mm, termination cross-section: 0,06 mm²...0,25 mm²
44423134:	Crimp contact, drilled, contact diameter: 0,6 mm, termination cross-section: 0,06 mm²...0,34 mm²
44423135:	Crimp contact, drilled, contact diameter: 0,6 mm, termination cross-section: 0,34 mm²...0,5 mm²

44423100	DATA SHEET	
Valid from: 28.03.2019	EPIC® M17 SIGNAL D6	

Drawings and dimensions of the connector:



Application range:

Plant engineering; measurement and control technology; apparatus construction

Remark:

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: STKU3/PDP Released: IVSE1/PDP	Document: DB44423100EN Version: 02	Page 4 of 4
---	---------------------------------------	-------------