

|                           |                     |                                                                                     |
|---------------------------|---------------------|-------------------------------------------------------------------------------------|
| 52023340                  | <b>DATA SHEET</b>   |  |
| Valid from:<br>03.07.2018 | <b>SILVYN® EE-K</b> |                                                                                     |

The SILVYN® LKI-M is a plastic terminal sleeves for protective conduit. They can used in the machine and plant constructions and prevents cable injury.  
SILVYN® EE-K is also used in products, like SILVYN® USK and SILVYN® MSK.



|                           |                                                                  |
|---------------------------|------------------------------------------------------------------|
| <b>Material:</b>          | Polypropylene                                                    |
| <b>Resistance:</b>        | To gas, oil, fat, alkalises, acids,<br>bases and common solvents |
| <b>Temperature range:</b> | -10°C up to +110°C                                               |
| <b>Colour:</b>            | Grey                                                             |



**Norm Reference:**

**Notes:** Free of halogen, cadmium and phosphor  
Self-extinguishing HB in acc. to UL 94

**Protection class:** IP 65 acc. EN 60529

**Dimensions table:**

| Part No.  | Part name       | Inner diameter<br>mm | Suitable Conduit diameter<br>mm |       |
|-----------|-----------------|----------------------|---------------------------------|-------|
|           |                 |                      | inner                           | outer |
| 5202 3340 | SILVYN® EE-K 10 | 6                    | 7                               | 10    |
| 5202 3350 | SILVYN® EE-K 14 | 9                    | 10                              | 14    |
| 5202 3360 | SILVYN® EE-K 17 | 11,5                 | 13                              | 17    |
| 5202 3370 | SILVYN® EE-K 19 | 13                   | 15                              | 19    |
| 5202 3380 | SILVYN® EE-K 21 | 14,5                 | 16                              | 21    |
| 5202 3390 | SILVYN® EE-K 27 | 19,5                 | 21                              | 27    |
| 5202 3400 | SILVYN® EE-K 36 | 26,5                 | 29                              | 36    |
| 5202 3410 | SILVYN® EE-K 45 | 36                   | 38                              | 45    |
| 5202 3430 | SILVYN® EE-K 56 | 45,5                 | 48                              | 56    |

**Suitable Conduit:**  
SILVYN® FPS  
SILVYN® FD-PU  
SILVYN® SP  
SILVYN® SP-PU

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

|                                                 |                                       |             |
|-------------------------------------------------|---------------------------------------|-------------|
| Creator: M. Wegerer /PDP<br>Released: DAMU1/PDP | Document: DB52023340EN<br>Version: 01 | Page 1 of 1 |
|-------------------------------------------------|---------------------------------------|-------------|