

55502710	DATA SHEET	
Valid from: 03.07.2018	SILVYN® LGS-2	

SILVYN® LGS-2 is a two part conduit gland made of nickel plated brass for swivel applications.

The conduit gland can be used in outdoor areas and in mechanical demanding environments.



Material: Brass, nickel plated

Features: High tensile strength
Oil resistant
Corrosion resistant

Temperature range: -50°C up to +300°C

Norm Reference:



Protection class: IP 54

Dimension table:

Part No.	Description	NW	Thread	Inner Ø mm	Thread length mm	Length mm	SW
5550 2710	SILVYN® LGS-2 PG 7	10	PG 7	5,6	8,0	30,2	13
5550 2720	SILVYN® LGS-2 PG 9	12	PG 9	8,5	8,0	32,2	17
5550 2730	SILVYN® LGS-2 PG 11	16	PG 11	11,5	10,0	34,2	22
5550 2740	SILVYN® LGS-2 PG 13,5	16	PG 13,5	15,3	10,0	35,5	24
5550 2750	SILVYN® LGS-2 PG 16	20	PG 16	15,3	10,0	35,5	24
5550 2760	SILVYN® LGS-2 PG 21	25	PG 21	19,1	12,0	43,7	29
5550 2770	SILVYN® LGS-2 PG 29	32	PG 29	26,2	13,0	48,0	38
5550 2780	SILVYN® LGS-2 PG 36	40	PG 36	34,2	14,0	51,2	48
5550 2790	SILVYN® LGS-2 PG 48	63	PG 48	54,5	16,0	61,2	70

Suitable conduit: SILVYN® LCC-2
SILVYN® LCCH-2

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB55502710EN Version: 02	Page 1 of 1
---	---------------------------------------	-------------