

6181 1200	DATA SHEET	
Valid from: 14.05.2018	SILVYN® KLICK-D	

SILVYN® KLICK-D is a cover for the conduit holder SILVYN® KLICK-S and prevented for disassembling.

Material:

Polyamide 6

Technical Features:

Nominal wide

NW 7 up to NW 48

Temperature range

-40°C up to +105°C

Additional features:

Fire classification

V2 acc. to UL94

Free of halogen und phosphorus

UV-Resistant

SILVYN® KLICK-D black

Colour:

Grey

Black



Approbation:



Suitable conduits:

SILVYN® KLICK-S

SILVYN® KLICK-V

Dimension table:

Part No.	Nominal width NW	Width mm	Plug distance mm	Cover High mm	High mm	Weight g
SILVYN® KLICK-D grey						
6181 1200	7 / 10	20,0	14,0	2,0	5,0	1,2
6181 1260	12	22,0	16,0	2,0	5,0	1,3
6181 1210	14 / 17	28,0	22,0	2,0	5,0	1,6
6181 1220	23	35,0	29,0	2,0	5,0	1,8
6181 1230	29	42,0	36,0	2,0	5,0	2,2
6181 1240	36	54,0	48,0	2,0	5,0	2,7
6181 1250	48	67,5	61,5	2,0	5,0	3,4
SILVYN® KLICK-D black						
6181 1205	7 / 10	20,0	14,0	2,0	5,0	1,2
6181 1265	12	22,0	16,0	2,0	5,0	1,3
6181 1215	14 / 17	28,0	22,0	2,0	5,0	1,6
6181 1225	23	35,0	29,0	2,0	5,0	1,8
6181 1235	29	42,0	36,0	2,0	5,0	2,2
6181 1245	36	54,0	48,0	2,0	5,0	2,7
6181 1255	48	67,5	61,5	2,0	5,0	3,4

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: MAU1/PDP Released: DAMU1/PDP	Document: DB61811200EN Version: 01	Page 1 of 1
--	---------------------------------------	-------------