



DATA SHEET	0162006
IEC compensating cable KN 4 L-S 2x1,5 oval	valid from : 01.12.2008

Application

The compensating cable KN 4 L-S 2 x 1,5 mm² is a glass fibre insulated cable which transmits the thermoelectric voltage of NiCr/Ni thermocouples. It is for fixed installation in dry rooms and may only be installed outdoors with UV- and humidity protection and in observation of the max. permitted temperature range. The steel wire armouring serves as mechanical protection.

Design

Conductor	1,5 mm ² (48 x 0,20 mm)
Conductor material	KCA alloying, accuracy class 2 according IEC 60584 Positive conductor: Fe (iron) Negative conductor: CuNi (cupronickel)
Core insulation	Glass fibre covering
Core identification	Positive conductor: green marked Negative conductor: white marked
Core layering	Cores parallel next to each other
Outer sheath	Glass fibre braiding with interweaved green identification thread
Armouring	Galvanized steel wire braiding with interweaved green identification thread

Electrical properties

Limiting deviation class 2	± 100 µV (± 2,5 °C) / measuring point temperature +900 °C
----------------------------	---

Mechanical and thermal properties

Temperature range	occasional flexing: -25 °C up to +200 °C
Minimum bending radius	occasional flexing: 15 x cable diameter
Flammability	flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2

Originator: Frank Hörtnagl / PD-KL Approved: Werner Körner / TE	Document: DB0162006EN	page 1 of 1
--	-----------------------	-------------

All deviations from this specification are subject to explicit consent of U.I.LAPP GmbH. All rights reserved acc. to DIN 34.
No.: 0019/0408