

55507350	DATA SHEET	
Valid from: 03.07.2018	SILVYN® FPAX Y	

SILVYN® FPAX Y is a Y-hook conduit gland with fast fit and an inner seal for a safety assembling. For the demounting we are recommending to use a screwdriver. The gland is suitable for SILVYN® FPAS and can be used in the machine- and plant constructions.



Material:	Body – PA66 Seal – Polyester
Features:	Fast assembling Anti-vibration Suitable for fine and coarse conduits High mechanical strength
Temperature range:	-50°C up to +135°C
Colour:	Black (UV-Resistant)

Norm Reference:



Note: Free of halogen, Sulphur and phosphorus

Protection class: IP66, IP67, IP68 (2bar) and IP69 K

Dimension table:

Part no.	Part name	Conduit Ø		Total		holes	
		Input value mm	Output value mm	length mm	wide mm	distance mm	Ø mm
5550 7350	SILVYN® FPAX Y	16	2x13	77	49	24	4
5550 7351	SILVYN® FPAX Y	21	2x16	89	59	32	5
5550 7352	SILVYN® FPAX Y	28	2x21	93	67	49	6
5550 7353	SILVYN® FPAX Y	34	2x28	116	90	48	6,5

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB55507350EN Version: 01	Page 1 of 1
---	---------------------------------------	-------------