

61221035	DATA SHEET	
Valid from: 03.07.2018	SILVYN® TC	

The SILVYN® TC is a conduit, which can be applied without screw connection - particularly for thin-walled and thread less housings. SILVYN® TC can be attached with a simple counter nut.

Nevertheless we recommend the suitable counter nut our SKINTOP® GMP-GL-M in black.



Material: PA6

Features: Flexible
Mechanical protection / Dimension stable
Quick and easy installation
Abrasion resistant

Resistance: To fuels, mineral oils, lubricants, alkalis and most commercial solvents

Temperature range: -40°C up to +120°C (short term to 150°C)

Colour: Schwarz (UV-Resistant)

Notes: Free of halogen
None declaration-requiring material
Self-extinguishing HB acc. to UL94

Protection class: IP68
We recommend using an additional sealing to maximize the IP rating

Dimension table:

Part no.	Part name	Nominal size	Diameter mm		Thread
			inner	outer	
6440 0823	SILVYN® TC	7,5	6,6	10,0	M 10x1,0
6440 0824	SILVYN® TC	8,5	9,8	12,8	M 12x1,5
6440 0825	SILVYN® TC	12	12,3	15,7	M 16x1,5
6122 1035	SILVYN® TC	17	16,6	21,2	M 20x1,5
6440 0650	SILVYN® TC	22	23,1	28,4	M 25x1,5
6440 0651	SILVYN® TC	26	28,9	34,5	M 32x1,5
6440 0826	SILVYN® TC	37	34	42,2	M 40x1,5
6440 0827	SILVYN® TC	50	45,6	53,8	M 50x1,5

Suitable: SKINDICHT® JT PTFE (metric)
SKINTOP® GMP-GL-M
SILVYN® SPLIT COS
SILVYN® FLACHDICHTUNG
SILVYN® SCHLAUCHSCHERE

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB61221035EN Version: 03	Page 1 of 1
---	---------------------------------------	-------------