

RJ45 coupling - CUC-F-D1ZNI-S/R4GC8 - 1419022

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RJ45 coupling, type: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT6, material: Zinc die-cast, connection method: Female

Product Description

Freenet system

Your advantages

- ☒ Compact design
- ☒ Rugged design



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 251455
GTIN	4055626251455

Technical data

Mechanical characteristics

Connection method	Female
Number of slots	2
Transmission speed	1 Gbps
Rated current	1.5 A
Transmission characteristics (category)	CAT6

Ambient conditions

Ambient temperature (operation)	-10 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

Material data

Contact surface material	Gold over nickel
Contact material	Spring steel

RJ45 coupling - CUC-F-D1ZNI-S/R4GC8 - 1419022

Technical data

Material data

Housing material	Zinc die-cast
------------------	---------------

Electrical characteristics


Number of positions	8
GRP transmission properties	CAT6
Transmission speed	1 Gbps
Frequency range	250 MHz
Rated current	1.5 A
Rated voltage (III/3)	72 V (DC)

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



RJ45 socket insert, Freenet system

Approvals

Approvals

Approvals

EAC

Ex Approvals

RJ45 coupling - CUC-F-D1ZNI-S/R4GC8 - 1419022

Approvals

Approval details

EAC		B.01742
-----	---	---------

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>