



Wysokość boku 60

Łuk regulowany Magic



Typ	Wym. L mm	Szerokość mm	Wym. L mm	Grubość blachy mm	Opak. szt.	Waga kg/100 szt.	
RBMV 610 FS	340	100	340	1	1	75,9	6040 48 0
RBMV 615 FS	420	150	420	1	1	112,4	6040 48 2
RBMV 620 FS	490	200	490	1	1	163,2	6040 48 4
RBMV 630 FS	640	300	640	1,25	1	291,7	6040 48 6
RBMV 640 FS	820	400	820	1,25	1	463,2	6040 48 8
RBMV 650 FS	960	500	960	1,5	1	658,5	6040 49 0
RBMV 660 FS	1120	600	1120	1,5	1	899,2	6040 49 2



Stal

zł/szt.

FS ocynkowane metodą Sendzimira

Regulowany łuk 0° - 90° z systemem szybkozłączy. Do wszystkich koryt kablowych o wysokości boku 60 mm.

Łuk regulowany Magic



Typ	Wym. L mm	Szerokość mm	Wym. L mm	Grubość blachy mm	Opak. szt.	Waga kg/100 szt.	
RBMV 610 FT	340	100	340	1	1	82,8	6040 50 0
RBMV 615 FT	420	150	420	1	1	127,6	6040 50 2
RBMV 620 FT	490	200	490	1	1	178	6040 50 4
RBMV 630 FT	640	300	640	1,25	1	386,3	6040 50 6
RBMV 640 FT	820	400	820	1,25	1	619,6	6040 50 8
RBMV 650 FT	960	500	960	1,5	1	1044,7	6040 51 0
RBMV 660 FT	1120	600	1120	1,5	1	1427,2	6040 51 2

Stal

zł/szt.

FT ocynkowane metodą ogniowo-zanurzeniową

Regulowany łuk 0° - 90° z systemem szybkozłączy. Do wszystkich koryt kablowych o wysokości boku 60 mm.