

Product type designation

CP 1613 A2

COMMUNICATION PROCESSOR CP 1613 A2 PCI CARD
(32BIT;33MHZ/66MHZ; 3.3V/5V UNIVERSAL KEY) FOR
CONNECTION TO IND. ETHERNET (10/100MBIT/S) WITH ITP AND
RJ 45 PORT VIA HARDNET-IE S7 AND S7-REDCONNECT.
SUPPORT FOR OPERATING SYSTEM SEE SIMATIC NET SW



Transmission rate

Transfer rate	10, 100
---------------	---------

Interfaces

Number of electrical connections	
• at the 1st interface / acc. to Industrial Ethernet	2
Type of electrical connection	
• at the 1st interface / acc. to Industrial Ethernet	RJ45 port / 15-pin ITP connection

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	
• 1 / from backplane bus	5 V
• 2 / from backplane bus	12 V
Relative symmetrical tolerance / at DC	
• at 5 V	5 %
• at 12 V	5 %
Consumed current	
• 1 / from backplane bus / at DC / maximum	0.45 A

• 2 / from backplane bus / at DC / maximum	0.5 A
Power loss [W]	4 W
Permitted ambient conditions	
Ambient temperature	
• during operation	5 ... 55 °C
• during storage	-20 ... +60 °C
• during transport	-20 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP00
Design, dimensions and weight	
Module format	PCI
Width	21.6 mm
Height	107 mm
Depth	167 mm
Net weight	140 g
Number of plug-in cards of same design / plug-in / per PC station	4
Number of units / Note	-
Performance data	
Performance data / open communication	
Software / for open communication / by means of SEND/RECEIVE / required	Yes, HARDNET-IE S7 (S7-1613)
Number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	120
Performance data / S7 communication	
Software / for S7 communication / required	Yes, HARDNET-IE S7 (S7-1613)
Number of possible connections / for S7/PG communication / maximum	120
Number of possible connections / for optimized S7 communication / maximum	40
Performance data / multi-protocol mode	
Number of active connections / with multi-protocol mode	120
Number of configurable connections / per PC station	207
Performance data / PROFINET CBA	
Software / for PROFINET CBA communication / required	Yes, PN CBA OPC server
Number of remote connection partners / with PROFINET CBA	228
Number of connections / with PROFINET CBA / total	10000

Product functions / management, configuration	
Product function / MIB support	Yes
Protocol / is supported	
• SNMP v1	Yes
• SNMP v3	No
• DCP	Yes
• LLDP	No
Configuration software / required	Included in the scope of delivery of the required software product
Configuration software / for PROFINET CBA / required	Yes, SIMATIC iMAP
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher-level designation/location designation	Yes
• I&M2 - installation date	No
• I&M3 - comment	No
• I&M4 - signature	No
• I&M4 - OEM data	No

Product functions / Redundancy	
Software / for redundancy function / required	Yes, HARDNET-IE S7-REDCONNECT for communication with SIMATIC S7 H systems

Product functions / Time	
Product function / SICLOCK support	Yes
Protocol / is supported / NTP	No

Standards, specifications, approvals	
Standard	
• for EMC	2004/108/EC
• for safety / from CSA and UL	CAN/CSA C22.2 & UL 60950-1, UL 1950
• for emitted interference	EN 61000-6-3, EN 61000-6-4
• for interference immunity	EN 61000-6-1, EN 61000-6-2
Certificate of suitability	
• CE marking	Yes
• C-Tick	Yes

Further Information / Internet Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	http://www.siemens.com/industrial-controls/mall
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb

- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

10/14/2016