

INITIATOR TERMINAL (L+,L-,A) W/O LED, SPRING-L. TERM.  
SZ1.5SQMM, 5MM



Figure similar

| Model                                                  |               |
|--------------------------------------------------------|---------------|
| Design of LED initiator/actuator terminal              | no            |
| Design of terminal / Terminal levels internally linked | No            |
| General technical data                                 |               |
| Insulation material                                    | thermoplastic |
| Terminal contact spacing                               | 5 mm          |
| Protection class                                       |               |
| Combustibility class acc. to UL 94                     | V2            |
| Main circuit                                           |               |
| Operating voltage / rated value                        | 64 V          |
| Operating current / rated value                        | 10 A          |
| Appearance                                             |               |
| Color                                                  | grey          |
| • of the light source                                  | without       |
| Product details                                        |               |

|                                     |    |
|-------------------------------------|----|
| Product feature / Infeed function   | No |
| <b>Product component</b>            |    |
| • required / connection plate       | No |
| • PE connection                     | No |
| • Shield connection                 | No |
| • Disconnecter                      | No |
| Product feature / cross-connectable | No |

|                                                |   |
|------------------------------------------------|---|
| <b>Number</b>                                  |   |
| Number of terminal levels                      | 5 |
| Number of terminal points / per terminal level | 1 |

|                                                       |                        |
|-------------------------------------------------------|------------------------|
| <b>Connections</b>                                    |                        |
| <b>Connectable conductor cross-section / stranded</b> |                        |
| • minimum                                             | 1.5 mm <sup>2</sup>    |
| • maximum                                             | 1.5 mm <sup>2</sup>    |
| <b>Connectable conductor cross-section</b>            |                        |
| • solid                                               |                        |
| — minimum                                             | 1.5 mm <sup>2</sup>    |
| — maximum                                             | 1.5 mm <sup>2</sup>    |
| • finely stranded                                     |                        |
| — with core end processing / minimum                  | 1.5 mm <sup>2</sup>    |
| — with core end processing / maximum                  | 1.5 mm <sup>2</sup>    |
| — without core end processing / minimum               | 1.5 mm <sup>2</sup>    |
| — without core end processing / maximum               | 1.5 mm <sup>2</sup>    |
| <b>Type of electrical connection</b>                  |                        |
| • 1                                                   | spring-loaded terminal |
| • 2                                                   | spring-loaded terminal |
| Position / of the terminal                            | top                    |

|                                   |                |
|-----------------------------------|----------------|
| <b>Mechanical Design</b>          |                |
| Mounting type                     | DIN rail 35 mm |
| Material / of the insulating body | Thermoplast    |

|                                                  |                   |       |
|--------------------------------------------------|-------------------|-------|
| <b>Certificates</b>                              |                   |       |
| Design tested acc. to type of protection / EEx e | No                |       |
| General Product Approval                         | Test Certificates | other |



[sonstig](#)

[Umweltbestätigung](#)

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WA2011-3KE10>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/8WA2011-3KE10/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WA2011-3KE10](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA2011-3KE10)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>