

Data sheet

6XV1830-0MH10

Product type designation

Product description

SIENOPYR FR ship cable

Bus cable (2-core), sold by the meter, unassembled
SIMATIC NET, PROFIBUS SHIPBOARD CABLE SIENOPYR,
COPPER CABLE, FOR WIRING ON SHIPBOARD AND
OFFSHORE, SOLD BY THE METER MAX. CONSIGNMENT: 1000
M MIN. ORDER QUANTITY: 20 M



Suitability for use

Cable for fixed installation on ships and offshore facilities in all enclosed spaces and on open decks. This cable cannot be used for permanent installation in water.

Cable designation

M-02Y (ST) CH X 1 x 2 x 0,35 100 V

Electrical data

Damping ratio per length

• at 9.6 kHz / maximum	0.003 dB/m
• at 38.4 kHz / maximum	0.005 dB/m
• at 4 MHz / maximum	0.022 dB/m
• at 16 MHz / maximum	0.045 dB/m

Impedance

• Rated value	150 Ω
• at 9.6 kHz	250 Ω
• at 38.4 kHz	185 Ω
• at 3 MHz ... 20 MHz	150 Ω

Relative symmetrical tolerance

• of the characteristic impedance at 9.6 kHz	10 %
--	------

• of the characteristic impedance at 38.4 kHz	10 %
• of the characteristic impedance at 3 MHz ... 20 MHz	10 %
Loop resistance per length / maximum	110 mΩ/m
Insulation resistance coefficient	16000 GΩ·m
Operating voltage • RMS value	100 V

Mechanical data

Number of electrical cores	2
Design of the shield	Overlapped aluminum-clad foil, sheathed in a braided screen of tin-plated copper wires
Type of electrical connection / FastConnect	No
Outer diameter • of inner conductor • of the inner sheath of the cable • of cable sheath • of cable sheath / Note	0.67 mm 8 mm 9.8 mm Outer diameter > 8 mm: Bus connectors can only be connected after removing the outer cover
Symmetrical tolerance of the outer diameter / of cable sheath	0.5 mm
Material • of the wire insulation • of the inner sheath of the cable • of cable sheath	PE Halogen-free polymer (HM4) Halogen-free, cross-linked polymer
Color • of the insulation of data wires • of cable sheath	red/green Black
Bending radius • with single bend / minimum permissible • with multiple bends / minimum permissible	98 mm 196 mm
Tensile load / maximum	100 N
Weight per length	110 kg/km

Permitted ambient conditions

Ambient temperature • during operation • during storage • during transport • during installation • Note	-35 ... +80 °C -35 ... +80 °C -35 ... +80 °C -15 ... +80 °C Electrical properties measured at 20 °C, tests according to DIN 47250 part 4 respectively DIN VDE 0472
Ambient condition / for operation	At ambient temperatures below -15 °C, the cable must not be subjected to any movements other than the normal vibration levels encountered on board ship

Burning behavior	flame resistant according to IEC 60332-3-24, IEC 607542, IEC 61031, DIN VDE 0472 Part 805 Prüftart B
Chemical resistance • to mineral oil • to grease • to water	resistant to diesel fuel according to DIN VDE 51601, ASTM oil No. 2 according to DIN 53521, oil, NATOCode 0178, BWTL 91500031/2 according to VG 95214 Part 4, hydraulic fluid, NATOCode H515, BWTL 91500020 according to VG 95214 Part 4, cold cleaning solvent, BW-TL 68500017 according to VG 95214 Part 4, deionized water according to VG 95214 Part 4, deionized water with 3.5% NaCl resistant conditional resistance
Radiological resistance / to UV radiation	resistant

Product properties, functions, components / general

Product feature • halogen-free • silicon-free	Yes Yes
--	------------

Standards, specifications, approvals

UL/ETL listing / 300 V Rating	No
UL/ETL style / 600 V Rating	No
Marine classification association • American Bureau of Shipping Europe Ltd. (ABS) • Bureau Veritas (BV) • Det Norske Veritas (DNV) • Germanische Lloyd (GL) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS)	No No Yes Yes Yes No No

Further Information / Internet Links

Internet-Link • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAX Download Manager • to website: Industry Online Support	http://www.siemens.com/snst http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
--	---

last modified: 10/12/2016