


Obejma kabłąkowa

Obejma kabłąkowa (obejma BBS)



Typ	Zakres mocowa- nia D mm	Opak. szt.	Waga kg/100 szt.	
2056W 12 FT	8-12	100	4,45	1180 12 6
2056W 16 FT	12-16	100	4,89	1180 16 9
2056W 22 FT	16-22	100	5,7	1180 22 3
2056W 28 FT	22-28	100	7,8	1180 28 2
2056W 34 FT	28-34	100	9,4	1180 34 7
2056W 40 FT	34-40	100	10	1180 40 1
2056W 46 FT	40-46	100	12,8	1180 46 0
2056W 58 FT	52-58	50	17,1	1180 58 4
2056W 64 FT	58-64	50	18,6	1180 64 9
2056W 52 FT	46-52	100	13,6	1180 52 5
2056W 70 FT	64-70	50	18,5	1180 68 1
2056W 76 FT	70-76	25	20,6	1180 76 2
2056W 82 FT	76-82	25	22	1180 82 7
2056W 90 FT	82-90	25	26,2	1180 90 8

St Stal

zi/100 szt.

FT ocynkowane metodą ogniowo-zanurzeniową

Pasuje do kątowników o długości ramion 40 mm.

Obejma i śruba ze stali ocynkowanej ogniowo.

Wanienka dociskowa z polipropylenu, bezhalogenowa, kolor jasnoszary RAL 7035.

d	A	B	C	G	t	x	H	L
mm	mm	mm	mm		mm	mm	mm	mm
8 - 12	23	16	34	M6	1,5	5	74	27
12 - 16	23	20	34	M6	1,5	5	78	27
16 - 22	23	27	34	M6	1,5	5	85	27
22 - 28	23	33	34	M6	2	5	91	27
28 - 34	23	39	34	M8	2	5,5	99	31,5
34 - 40	23	45	34	M8	2	5,5	105	31,5
40 - 46	25	51	40	M8	2,5	6,5	111	31,5
46 - 52	25	57	40	M8	2	6,5	117	32,5
52 - 58	25	64	40	M8	2,5	6,5	123	32,5
58 - 64	25	70	40	M8	2,5	6,5	130	32,5
64 - 70	25	76	40	M8	2,5	6,5	136	32,5
70 - 76	25	82	40	M8	2,5	6,5	143	38,5