


## Obejma kabłąkowa (obejma BBS)



| Typ           | Zakres<br>mocowa-<br>nia D<br>mm | Opak.<br>szt. | Waga<br>kg/100 szt. |           |
|---------------|----------------------------------|---------------|---------------------|-----------|
| 2056W 2 12 FT | 8-12                             | 50            | 5,15                | 1181 12 2 |
| 2056W 2 16 FT | 12-16                            | 50            | 5,7                 | 1181 16 5 |
| 2056W 2 22 FT | 16-22                            | 50            | 7,05                | 1181 21 1 |
| 2056W 2 28 FT | 22-28                            | 50            | 10,35               | 1181 28 9 |
| 2056W 2 34 FT | 28-34                            | 50            | 11,6                | 1181 34 3 |
| 2056W 2 40 FT | 34-40                            | 25            | 12,7                | 1181 40 8 |
| 2056W 2 46 FT | 40-46                            | 25            | 16,75               | 1181 46 7 |
| 2056W 2 52 FT | 46-52                            | 25            | 18,2                | 1181 52 1 |
| 2056W 2 58 FT | 52-58                            | 25            | 23                  | 1181 58 0 |

St Stal

**FT** ocynkowane metodą ogniowo-zanurzeniową

Pasuje do kątowników o długości ramion 40 mm.

Obejma i śruba ze stali ocynkowanej ogniowo.

Wanienka dociskowa z polipropylenu, bezhalogenowa, kolor jasnoszary RAL 7035.

| d       | A  | B  | C  | G  | t   | x   | H   | L    |
|---------|----|----|----|----|-----|-----|-----|------|
| mm      | mm | mm | mm | mm | mm  | mm  | mm  | mm   |
| 8 - 12  | 23 | 16 | 34 | M6 | 1,5 | 5   | 88  | 34   |
| 12 - 16 | 23 | 20 | 34 | M6 | 1,5 | 5   | 96  | 34   |
| 16 - 22 | 23 | 27 | 34 | M6 | 1,5 | 5   | 109 | 34   |
| 22 - 28 | 23 | 33 | 34 | M6 | 2   | 5   | 121 | 34   |
| 28 - 34 | 23 | 39 | 34 | M8 | 2   | 5,5 | 135 | 37,5 |
| 34 - 40 | 23 | 45 | 34 | M8 | 2   | 5,5 | 147 | 37,5 |
| 40 - 46 | 25 | 51 | 40 | M8 | 2   | 5,5 | 160 | 37,5 |
| 46 - 52 | 25 | 57 | 40 | M8 | 2   | 6,5 | 172 | 38,5 |
| 52 - 58 | 25 | 64 | 40 | M8 | 2,5 | 6,5 | 185 | 38,5 |