

Śruba z łbem sześciokątnym



Typ	Gwint	Wymiar mm	Wym. L mm	Wym. d mm	SW mm	Opak. szt.	Waga kg/100 szt.	
342 M8X20 G	M8	M 8 x 20	20	8	13	100	1,23	3158 20 9
342 M8X25 G	M8	M 8 x 25	25	8	13	100	1,39	3158 24 1
342 M8X30 G	M8	M 8x30	30	8	13	100	1,55	3158 30 6
342 M10X20 G	M10	M 10 x 20	20	10	17	100	2,32	3160 20 3
342 M10X30 G	M10	M 10 x 30	30	10	17	100	2,82	3160 30 0
342 M10X40 G	M10	M 10 x 40	40	10	17	50	3,24	3160 40 8
342 M10X50 G	M10	M 10 x 50	50	10	17	50	3,82	3160 50 5
342 M10X60 G	M10	M 10 x 60	60	10	17	50	4,33	3160 60 2
342 M12X30 G	M12	M 12x30	30	12	19	50	4,02	3162 30 3
342 M12X40 G	M12	M 12x40	40	12	19	50	4,74	3162 40 0
342 M12X50 G	M12	M 12x50	50	12	19	50	5,45	3162 50 8

St

Stal

zł/100 szt.

G ocynkowane galwanicznie

Śruba z łbem sześciokątnym wg ISO 4017 z gwintem metrycznym. Klasa wytrzymałości min 5,6.

