


Obejma kabłkowa



Typ	Zakres mocowa- nia D mm	Opak. szt.	Waga kg/100 szt.	
2056 M 12 VA	8-12	50	3,2	1159 71 2
2056 M 16 VA	12-16	50	3,5	1159 71 6
2056 M 22 VA	16-22	50	4,4	1159 72 2
2056 M 28 VA	22-28	25	6,1	1159 72 8
2056 M 34 VA	28-34	25	7,7	1159 73 4
2056 M 40 VA	34-40	25	8,6	1159 74 0
2056 M 46 VA	40-46	25	9,6	1159 74 6
2056 M 52 VA	46-52	25	10,4	1159 75 2
2056 M 58 VA	52-58	15	13,1	1159 75 8
2056 M 64 VA	58-64	15	14,5	1159 76 4
2056 M 70 VA	64-70	15	16,1	1159 77 0
2056 M 76 VA	70-76	10	18,3	1159 77 6

V2A Stal nierdzewna 1.4301

zł/100 szt.

Pasuje do wszystkich szyn profilowych C o szerokości szczeliny 16 - 17 mm;

Obejma, śruba i wianienka dociskowa ze stali nierdzewnej.

D	A	B	C	G	t	x	H	L
mm	mm	mm	mm		mm	mm	mm	mm
8-12	23	16	30	M6	1,5	3,5	44	32,5
12-16	23	20	30	M6	1,5	3,5	44	32,5
16-22	23	27	30	M6	1,5	4,5	60	46,5
22-28	23	33	30	M6	2	4,5	58	46,5
28-34	23	39	35	M8	2	5	66	44
34-40	23	45	35	M8	2	5	72	44
40-46	23	51	35	M8	2	5	79	44
46-52	23	57	35	M8	2	5	86	44
52-58	23	64	35	M8	2,5	5	93	44
58-64	23	70	35	M8	2,5	5	99	56
64-70	25	76	35	M8	2,5	5	106	56
70-76	25	82	40	M8	2,5	5	114	56