



SIPLUS ET200S TM-E15C24-01 -40 ... +70 DEGREES C WITH CONFORMAL COATING BASED ON 6ES7193-4CB30-0AA0 5 PIECES AT EACH PACKAGING UNIT . FOR ELECTRONIC MODULES WIDTH 15MM, SPRING-LOAD TERMINALS 2X4 TERMINAL CONNECTIONS WITH TERMINAL LEAD TO AUX1, AUX1 IN LINE

Figure similar

Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	-40 °C; = Tmin
• max.	70 °C; = Tmax
Extended ambient conditions	
• relative to ambient temperature-atmospheric pressure-installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity	
— With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; Relative humidity, incl. condensation / frost permitted (no commissioning under condensation conditions)
Resistance	
— against biologically active substances / conformity with EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!

— against chemically active substances /
conformity with EN 60721-3-3

Yes; Class 3C4 incl. salt spray according to EN 60068-2-52
(degree of severity 3). The supplied connector covers must
remain on the unused interfaces during operation!

— against mechanically active substances /
conformity with EN 60721-3-3

Yes; Class 3S4 incl. sand, dust. The supplied connector covers
must remain on the unused interfaces during operation!

Dimensions

Width	15 mm
Height	132 mm
Depth	43 mm

Weights

Weight, approx.	65 g
-----------------	------

Scope of supply

Delivery quantity in pieces	5
-----------------------------	---

last modified: 10/28/2016