

Data Sheet

General and Commercial Data

Product Type	Interiors - Industrial Floodlights
Model	Highbay HP
Code	40207
Description	HIGHBAY HP 240W 90°0-10V 4K ED
EAN Code	8002219755612
Available Colors	Aluminium
Application	Production, Warehouses, Industrial Areas
Net Weight [kg]	7.5
Dimensions [mm]	360x189

Technical Characteristics

Volume [m3]	0.040572
Insulation Class	I
IP Code	65
Impact Resistance IK Rating	9
Fire Resistance [°C]	650
Material	Die-cast aluminium
Voltage [V]	230
Frequency [Hz]	50
Power Factor (cos(φ))	0.95
Luminaire Power [W]	240
Battery Life [h]	---
Luminaire Flux [lm]	34000
Luminous Efficacy [lm/W]	142
Range Ambient Temperature [°C]	-25 ÷ 50
Ballast	For constant current LED (Dimmable 1-10V)
Source	CCT 4000 K - CRI 80
Average Life [h]	50000
Source Flux [lm]	34000
Photobiological Risk Index (EN 62471)	Risk 0

Photometric Parameters


Measurement	40207o_LENS_90
CIE Code	[57,90,99,100,100]
Optics Type	Symmetrical

Notes


Possible Flux configurations [lm]: 34000
 Possible Power configurations [W]: 240
 Possible CCT configurations [K]: 4000

Norms

2014/35/EU
 2014/30/EU
 874/2012/CE
 2009/125/CE
 EN 62471
 CEI EN 60598-1
 CEI EN 60598-2-1



Codice Ordine	H	H1	Ø	Peso kg
40224-40204	167	108	300	3.9
40225-40205	167	108	300	4.5
40226-40206	189	125	360	7
40227-40207	189	125	360	7.5



Marks

