

Data Sheet

General and Commercial Data

Product Type	Exterior/Interior - Emergency Lighting
Model	Logica LED
Code	19410
Description	LOGICA LED LTO LG AR SE
EAN Code	8002219744852
Available Colors	Signal White RAL 9003
Application	Offices,Public Areas,Industrial Areas,Emergency Lighting
Net Weight [kg]	2.2
Dimensions [mm]	147x406x63
Pieces per Pack	6

Technical Characteristics

Volume [m3]	0.004704
Insulation Class	II
IP Code	65
Impact Resistance IK Rating	8
Fire Resistance [°C]	850
Material	Polycarbonate
Emergency Source Supply Type	Self-contained luminaire
Emergency Operation Mode	Non-maintained mode
Battery	2 x LTO 9.6V 1.2Ah
Diagnosis System	Luminaire with centralized diagnostic system
Test System for Emergency Lighting	Inhibition mode
Visibility Distance (EN1838) [m]	20
Voltage [V]	230
Source Current [A]	0.025
Frequency [Hz]	50
Power Factor (cos(fi))	0.83
Luminaire Power [W]	7
Luminaire Flux in Emergency [lm]	1100
Battery Life [h]	1
Range Ambient Temperature [°C]	-20 ÷ 45
Source	CCT 5000 K - CRI 80
Photobiological Risk Index (EN 62471)	Risk 0

Photometric Parameters



Measurement	19410e1h
CIE Code	[57,89,98,100,100]
Optics Type	Symmetrical

Notes

Flux SE[lm]: 1100/750/400 _____ Autonomy[h]: 1/1.5/3
 Flux SE AR[lm]: 2000/1500/800 _____ Autonomy AR[h]: 1/1.5/3

Norms

2014/35/EU
 2014/30/EU
 874/2012/CE
 2009/125/CE
 CEI EN 62034
 CEI EN 60598-2-2
 CEI EN 60598-2-22



Marks

