

Data Sheet

General and Commercial Data

Product Type	Interiors - Industrial Floodlights
Model	H-PRO
Code	40839
Description	RIF S 150W D SD 4K
EAN Code	8002219860323
Available Colors	Grey
Net Weight [kg]	7.7
Dimensions [mm]	425x413x121

Technical Characteristics

Volume [m3]	0.032299
Insulation Class	I
IP Code	66
Impact Resistance IK Rating	9
Fire Resistance [°C]	960
Material	Die-cast aluminium
Voltage [V]	230
Frequency [Hz]	50
Power Factor (cos(φ))	0.95
Luminaire Power [W]	153
Battery Life [h]	---
Luminaire Flux [lm]	22824
Luminous Efficacy [lm/W]	150
Range Ambient Temperature [°C]	-30 ÷ 60
Ballast	Constant current LED Smart driver (programmable)
Source	CCT 4000 K - CRI 80
Average Life [h]	70000
Source Flux [lm]	22824
Photobiological Risk Index (EN 62471)	Risk 0

Photometric Parameters


Measurement	40839o
CIE Code	[57,90,99,100,100]
Optics Type	Symmetrical

Notes

Possible Flux configurations [lm]: 22824
 Possible Power configurations [W]: 153
 Possible CCT configurations [K]: 4000

Norms

2014/35/EU
 2014/30/EU
 874/2012/CE
 2009/125/CE
 EN 62471
 CEI EN 60598-1
 CEI EN 60598-2-5



Marks

