



TRYTYKI SGT - naturalne

materiał: poliamid 6.6

temp. montażu: -10°C do +60°C

temp. pracy: -40°C do +85°C

wytrzymałość dielektryczna: 50kV/mm²

absorpcja wody: 2,5% (50% R.H., +23°C)

palność: UL-94 V2

tolerancja: ±5%



TYP	ROZMIAR [mm]	max/min ŚREDNICA [mm]	WYTRZYMAŁOŚĆ [kg]	OPAKOWANIE [szt]	
SGT-100MC	100x2,5	24/2	11	100	☐
SGT-140MC	135x2,5	35/2	11	100	☐
SGT-160MC	160x2,5	42/2	11	100	☐
SGT-200MC	200x2,5	55/2	11	100	☐
SGT-140IC	140x3,5	36/3	20	100	☐
SGT-200IC	200x3,5	55/3	20	100	☐
SGT-250IC	250x3,5	70/3	20	100	☐
SGT-300IC	280x3,5	80/3	20	100	☐
SGT-370IC	360x3,5	103/3	20	100	☐
SGT-190STC	200x4,5	51/3	28	100	☐
SGT-250STC	250x4,5	68/5	28	100	☐
SGT-280STC	280x4,5	76/5	28	100	☐
SGT-370STC	360x4,5	101/5	28	100	☐
SGT-430STC	430x4,5	123/5	28	100	☐
SGT-200HD	200x7,5	48/5	65	100	☐
SGT-300HD	280x7,5	76/5	65	100	☐
SGT-370HD	360x7,5	101/5	65	100	☐
SGT-430HD	450x7,5	130/20	65	100	☐
SGT-530HD	540x7,5	160/20	65	100	☐
SGT-750HD	750x7,5	222/32	65	100	☐
SGT-770HDL	780x9,0	235/22	80	100	☐
SGT-1170HDL	1220x9,0	375/40	80	100	☐
SGT-500EHD	500x12,5	140/10	120	50	☐
SGT-750EHD	750x12,5	222/40	120	50	☐



złącz

TRYTYT.COM!