

LM-BVS35

Zasilanie magistralne 35, szafa ster.

Nr art. 22115026

Power supply of LUXMATE bus line with max. 35 LUXMATE devices

Zastosowanie

For a smaller LUXMATE system or a bus domain with up to 35 LUXMATE devices, the smaller LM-BVS35 can be used as a bus power supply instead of the LM-BV.

Wskazówki dotyczące planowania

- The LM-BV product (art. no. 20 975 247) must be used for the supply of up to 100 LM devices.
- The LM-BVS35 replaces the LM-BVE bus power supply (art. no. 20 735 375).



Opis działania

The LM-BVS35 bus power supply provides the LUXMATE bus with 15V DC and thus maintains the information flow in the LUXMATE system. The operation status, any short circuits and activities on the bus are signalled by two LEDs.


Schemat połączeń



Wskazówki dotyczące montażu i instalacji

- The bus power supply is installed in switch and distribution cabinets.
- Up to 35 LUXMATE devices can be connected to one LM-BVS35, where all box units, e.g. the LM-SDED, count as four modules. However, multiple modules like LM-3DSIS or LM-2JSMX count only as one module.

Rozmiar



Dane techniczne

Napięcie znamionowe	230/240 V AC, 50/60 Hz
Dopuszczalne napięcie wejściowe	100 ... 264 V AC, 50 ... 60 Hz
Strata mocy	< 2 W
Wyjścia	
Terminale	
{failed}	IP20
Klasa ochronności	
Materiał obudowy	poliwęglan, bez halogenów, ognioodporny
Instalacja	Na szynie DIN typu O o szerokości 35 mm, zgodnej z EN 50022
Wymiary	2 jednostek dla 17,5mm
Dopuszczalna temperatura otoczenia Ta	0 °C ... + 50 °C
Weight	Ok. 0.09 kg

Tabliczka znamionowa/podłączenia

