




Oprawa bezpieczeństwa

LED emergency luminaire for escape route lighting with min. 1 lux compliant to EN 1838; Room height 2.2 to 7 m; 2 high power LEDs, neutral white 4,000 K; lens of polycarbonate; optimum thermal management via heat sink; Recessed ceiling luminaire for 40 mm ceiling cut-out and ceiling thicknesses from 1-25 mm; tool-free rapid luminaire installation through specially shaped retaining springs; tool-free replacement of battery and control unit; Cover ring diecast aluminium, powder-coated; housing colour white (close to RAL9016); Polypropylene (PP) gearbox for installation in ceiling recess; Luminaire with local battery supply for 1 h emergency lighting in maintained or non-maintained mode, with automatic test (auto-test) via the luminaire, optional central monitoring via DALI, display of luminaire status via status LED; NFC interface for addressing, configuration and maintenance via PROset Pen (article no.: 22170290) or PROset app; addressing also alternatively possible visually or via EZ-addressing; Maintained and non-maintained mode: +5°C to +35°C; power supply: 220-240 V AC (+/- 10%), 50-60 Hz; Luminaire input power: 4.7 W (with battery fast-charge in maintained mode); typical power (without battery charge): 3,5 W in maintained mode / 1,1 W in non-maintained mode; Non-maintained and maintained mode settable via jumper and NFC interface; IP20; SC1; Luminaire wired with halogen-free and silicone-free leads; Impact strength: IK04; Dimensions: Ø50 x 3 mm; weight: 0.26 kg; Robust, integrated battery with 3-year warranty. Valid according to terms of the manufacturer's warranty, available at https://www.zumtobel.com/media/downloads/Garantiebedingungen_DE.pdf; Battery warranty invalid if installation takes place three (3) months after delivery EXW (Incoterms 2010)




ZS_RES_F_PRO_MRCR_mini_E1D_ESC_WH.jpg



ZS_RES_M_PRO_MRCR_mini.wmf

Dystrybucja światła

STD - Standard



D43503_RESC_PRO_MRCR_MINI_ESC_E1D_WH.Idt

- Źródło światła: LED
- Strumień świetlny oprawy*: 255 lm
- Całkowity strumień "awaryjny": 255 lm
- Skuteczność oprawy*: 54 lm/W
- Współczynnik oddawania barw: 70
- Statecznik: 1 x 89800524 DRV EM TR LBS P ST DA 5W 2
- Tolerancja miejscowa barwy (initial Mac Adam): 5
- Średnia żywotność nominalna*: L95 100000h przy 25°C
- Moc oprawy*: 4,7 W Współczynnik mocy = 0,7
- Moc w trybie czuwania*: 1,2 W
- Wydajność ładowania: 1,25 W
- Znamionowa trwałość użytkowa: 1 h
- : D - Zamknięta IP2X

Patrz dodatkowe informacje na następnej stronie.

RESCLITE PRO MRCR mini IP20-40, do zabudowy w suficie



ZUMTOBEL

RESCLITE PRO MRCR MINI ESC E1D WH

42185661

Oprawa bezpieczeństwa